



## Product Line Laying Materials

Effective from 4/2025

**WAKOL®**  
Anspruch verbindet

Wakol GmbH  
Bottenbacher Straße 30  
D-66954 Pirmasens  
Tel. +49 6331 8001 131  
Fax +49 6331 8001 890  
www.wakol.com



Wakol GmbH  
Industriestraße 5  
A-6841 Mäder  
Tel. +43 5523 64 700  
Fax +43 5523 64 700 64  
www.wakol.at

Wakol Foreco srl  
Via Kennedy 75  
I-20010 Marcallo con Casone (MI)  
Tel. +39 02 9761 939  
Fax +39 02 9725 3021  
www.wakolforeco.it

Loba-Wakol, LLC  
2732 Hwy 74 West  
Wadesboro, NC 28170, USA  
Tel. +1 800 230 6456  
Fax +1 704 527 5922  
www.loba-wakol.com

Lecol Chemie B.V.  
Schutweg 6  
NL-5145 NP Waalwijk  
Tel. +31 416 566 540  
Fax +31 416 566 531  
www.lecol.nl

Wakol Adhesa AG/SA  
Bionstraße 5  
CH-9015 St. Gallen  
Tel. +41 31 9210 755  
Fax +41 31 9212 968  
www.wakoladhesa.ch

Loba-Wakol Polska Sp. z o.o.  
ul. Sławęcińska 16, Macierzysz  
PL-05-850 Ożarów Mazowiecki  
Tel. +48 22 436 24 20  
Fax +48 22 436 24 21  
www.loba-wakol.pl

Loba GmbH & Co. KG  
Leonberger Straße 56-62  
D-71254 Ditzingen  
Tel. +49 7156 357 220  
Fax +49 7156 357 221  
www.loba.de

PREPARING .....	4	
LEVELLING .....	8	
BONDING ELASTIC FLOORING .....	15	
BONDING LINOLEUM / TEXTILE FLOORING .....	21	
BONDING PARQUET / CORK FLOORING .....	25	
FIXING FLOORING .....	34	
LAYING CONDUCTIVE FLOORING .....	35	
UNDERLAYS / MATS / TILES .....	37	
TOOLS / ACCESSORIES .....	45	
WORKING CLOTHES / EQUIPMENT .....	57	
TABLES FOR INSTALLATION .....	60	
TROWEL NOTCH SIZES .....	74	
SYMBOLS / EXPLANATIONS .....	75	

Please always observe the Technical Information before processing.

## WAKOL MS 330 Silane Primer



### Area of application:

Ready-to-use 1-component MS primer for priming absorbent and non-absorbent subfloors, and to reinforce abraded resp. sanded concrete edges. Also for blocking higher residual humidity up to max. 5 CM% / 95 corresponding RH % in cement screeds without floor heating, up to max. 3 CM% / 85 corresponding RH % with floor heating, as well as up to max. 7 % by weight / 95 corresponding RH % without floor heating in concrete before laying Wakol MS Adhesives.

### Application method:

as primer with WAKOL Primer Roller or velour roller, as moisture barrier with WAKOL MS Special Roller or trowel notch size according to TKB A2

### Consumption:

approx. 80-120 g/m<sup>2</sup> as primer, approx. 250 g/m<sup>2</sup> as moisture barrier

### Drying time:

approx. 60 minutes

### Storage information:

not sensitive to frost

### Base:

MS polymer

### Order information:

361403 | 35284 – 10.0 kg – pallet: 60 pieces  
361404 | 35283 – 5.0 kg – pallet: 96 pieces

## WAKOL D 3080 Dispersion Moisture Barrier



### Area of application:

Dispersion primer for blocking higher residual humidity up to 5 CM% / 95 corresponding RH % in cement screeds without floor heating, up to max. 3 CM% / 85 corresponding RH % with floor heating before subsequent levelling with cement-based Wakol levelling compounds indoors.

### Application method:

WAKOL Primer roller or short haired velour roller

### Consumption:

1<sup>st</sup> application 60-75 g/m<sup>2</sup> 1:1 diluted,  
2<sup>nd</sup> application 100-120 g/m<sup>2</sup> undiluted

### Drying time:

1<sup>st</sup> application at least 30 minutes,  
2<sup>nd</sup> application at least 120 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

polymer dispersion

### Blue Angel:

DE-UZ 113

### Order information:

308005 | 35888 – 11.0 kg – pallet: 60 pieces

## WAKOL PU 280 Polyurethane Primer



### Area of application:

Ready-to-use 1-component polyurethane primer for priming absorbent and non-absorbent subfloors, and to reinforce abraded resp. sanded concrete edges. Also for capillary ascending humidity and higher residual humidity up to 6 CM % / 98 corresponding RH % in cement screeds without floor heating, on heated cement screeds up to max. 3 CM% / 85 corresponding RH % as well as on concrete up to max. 7,5% by weight / 98 corresponding RH %; applicable as moisture barrier on unheated cement screeds and concretes without prior moisture measurement.

### Application method:

WAKOL Primer Roller or short haired velour roller

### Consumption:

approx. 100-150 g/m<sup>2</sup> as primer, approx. 250-350 g/m<sup>2</sup> as moisture barrier

### Drying time:

approx. 40-50 minutes

### Storage information:

not below +5 °C, store in a cool place

### Base:

polyurethane resin

### Order information:

364003 | 35179 – 11.0 kg – pallet: 60 pieces  
364004 | 35178 – 5.0 kg – pallet: 96 pieces

## WAKOL D 3055 Parquet Primer



### Area of application:

Ready-to-use dispersion-based primer for priming absorbent cement- and calcium sulphate concrete as well as gypsum fibre boards before subsequent laying of parquet with Wakol parquet adhesives indoors.

### Application method:

WAKOL Primer Roller or velour roller

### Consumption:

approx. 100-150 g/m<sup>2</sup>

### Drying time:

on cement screeds following visible drying approx. 30 minutes, on calcium sulphate concrete and gypsum fibre boards after approx. 2 hours

### Storage information:

not below +5 °C, sensitive to frost

### Base:

polyurethane dispersion

### Blue Angel:

DE-UZ 113

### Order information:

305505 | 35892 – 10.0 kg – pallet: 60 pieces  
305506 | 36071 – 5.0 kg – pallet: 96 pieces

## WAKOL PU 235 Polyurethane Primer



### Area of application:

Ready-to-use 1-component polyurethane primer for priming absorbent and non-absorbent subfloors, and to reinforce abraded resp. sanded concrete edges. Also for capillary ascending humidity and higher residual humidity up to 6 CM % / 98 corresponding RH % in cement screeds without floor heating, on heated cement screeds up to max. 3 CM% / 85 corresponding RH % as well as on concrete up to max. 7,5% by weight / 98 corresponding RH %.

### Application method:

WAKOL Primer Roller or short haired velour roller

### Consumption:

approx. 100-150 g/m<sup>2</sup> as primer, approx. 250-350 g/m<sup>2</sup> as moisture barrier

### Drying time:

approx. 4-6 hours

### Storage information:

not below +5 °C, store in a cool place

### Base:

polyurethane resin

### Order information:

364103 | 35188 – 11.0 kg – pallet: 60 pieces

## WAKOL D 3045 Special Primer



### Area of application:

Ready-to-use dispersion-based primer to use as an adhesive bridge for Wakol levelling compounds on WAKOL PU 280 Polyurethane Primer, WAKOL PU 235 Polyurethane Primer or WAKOL MS 330 Silane Primer, cast asphalt and wooden material tiles, old waterproof adhesive residues as well as thoroughly cleaned ceramic tiles, natural stone flooring and terrazzo indoors.

### Application method:

WAKOL Primer Roller or velour roller

### Consumption:

approx. 100-150 g/m<sup>2</sup>

### Drying time:

approx. 30-60 minutes, approx. 60-120 minutes on wooden material tiles

### Storage information:

not below +5°C, sensitive to frost

### Base:

acrylate dispersion

### Order information:

304505 | 38507 – 12.0 kg – pallet: 40 pieces  
304506 | 36070 – 6.0 kg – pallet: 80 pieces



WAKOL D 3004 Primer Concentrate



**Area of application:**  
Dispersion-based primer concentrate for priming cement screed, calcium sulphate screed, cast asphalt screed, magnesite screed (with exclusively mineral-based additives), concrete, tiles, terrazzo, water resistant adhesive residues, wood planks, wooden material tiles, gypsum fibre boards as well as Wakol levelling and filling compounds before subsequent levelling indoors.

**Application method:**  
WAKOL Primer Roller or velour roller

**Consumption:**  
approx. 40-50 g/m² concentrate for diluted application,  
approx. 80-120 g/m² for undiluted application

**Drying time:**  
on cement screeds and concrete following visible drying;  
on cast asphalt, tiles, terrazzo and water resistant  
adhesive residues 30-60 minutes; on calcium sulphate  
screed, magnesite screed, wood planks, wooden material  
tiles and gypsum fibre boards 60 minutes

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
polymer dispersion

**Order information:**  
300405 | 36067 – 10.0 kg – pallet: 60 pieces  
300407 | 36069 – 5.0 kg – pallet: 96 pieces  
300409 | 36068 – 1.0 kg – pallet: 480 pieces; 40 boxes  
with 12 pieces

WAKOL PS 275 Concrete Repair Primer



**Area of application:**  
Ready-to-use primer to strengthen dry, porous, completely brittle, absorbent, cement based subfloors indoors.

**Application method:**  
WAKOL MS Special Roller or velour roller

**Consumption:**  
approx. 600 g/m², depending on the absorption of the  
subfloor

**Drying time:**  
3-5 days

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
sodium silica

**Order information:**  
361603 | 35204 – 11.0 kg – pallet: 60 pieces

WAKOL D 3003 Dispersion Primer



**Area of application:**  
Ready-to-use dispersion-based primer for priming cement screed, calcium sulphate screed, cast asphalt screed, magnesite screed (with exclusively mineral-based additives), concrete, gypsum fibre boards, water-resistant adhesive residues as well as Wakol levelling and filling compounds before subsequent levelling indoors.

**Application method:**  
WAKOL Primer Roller or velour roller

**Consumption:**  
approx. 90-140 g/m²

**Drying time:**  
on cement screeds and concrete following visible drying;  
on calcium sulphate screed and gypsum fibre boards after  
at least 60 minutes; on cast asphalt screed and water-  
resistant adhesive residues after approx. 30-60 minutes

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
polymer dispersion

**Blue Angel:**  
DE-UZ 113

**Order information:**  
300305 | 36066 – 10.0 kg – pallet: 60 pieces

WAKOL PS 205 Cast Resin



**Area of application:**  
Quick hardening polymer-modified two-component silica resin for renovating concrete subfloor cracks as well as for bonding studded boards, metal sections and synthetic or natural stone to absorbent and non-absorbent subfloors indoors.

**Mixture:**  
1:1 parts by volume

**Consumption:**  
depending on the scope of the repair work, for adhesive  
work approx. 200-300 g/m²

**Pot life:**  
15 °C approx. 13 min., 20 °C approx. 10 min.,  
25 °C approx. 8 min., 30 °C approx. 7 min.

**Hardening time:**  
15 °C approx. 40 min., 20 °C approx. 30 min.,  
25 °C approx. 22 min., 30 °C approx. 18 min.

**Storage information:**  
not below +10 °C, store in a dry place, sensitive to frost

**Base:**  
silica resin

**Order information:**  
360505 + 360405 | 41294 – 300 ml A-comp. + 300 ml  
B-comp. – pallet: 240 pieces each A+B; 40 boxes with  
6 pieces A+B + 6 x 20 corrugated connectors

WAKOL DL 3078 Conductive Primer



**Area of application:**  
Ready-to-use conductive dispersion-based primer for subsequent conductive laying of textile and elastic flooring. WAKOL DL 3078 replaces the laying of a copper band net.

**Application method:**  
WAKOL Primer Roller

**Consumption:**  
approx. 120-150 g/m²

**Drying time:**  
approx. 3-5 hours

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
acrylate dispersion

**Order information:**  
307803 | 25687 – 10.0 kg – pallet: 60 pieces

WAKOL R 4515 Tile Cleaner



**Area of application:**  
Cleaner for manual or machine application on old tiled floors for removal of layers of old care products and extreme dirt before subsequent laying.

**Mixture:**  
1 part WAKOL R 4515 + 3 parts water

**Consumption:**  
1.0 l WAKOL R 4515 / 20 m²

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
tensides

**Order information:**  
451505 | 34988 – 5.0 l – pallet: 128 pieces

WAKOL D 3060 Plastification Additive



**Area of application:**  
Ready-to-use dispersion for upgrading WAKOL Z 645 Filling Compound, WAKOL Z 640 Filling Compound, WAKOL Z 630 Levelling Compound, WAKOL Z 625 Levelling Compound, WAKOL Z 615 Levelling Compound, dust-reduced, WAKOL Z 610 Levelling Compound, dust-reduced, WAKOL A 850 Filling Compound and WAKOL A 830 Levelling Compound to increase adhesion, flexibility and reduction of shrinkage tension for applications indoors.

**Mixture:**  
approx. 4.5-8.0 l WAKOL D 3060 + 20/25 kg of Levelling Compound

**Storage information:**  
not below +5 °C; sensitive to frost

**Base:**  
polyacrylate dispersion

**Order information:**  
306003 | 35890 – 10.0 kg – pallet: 60 pieces

WAKOL Z 715 Quick Setting Levelling Compound



**Area of application:**  
Cement-based quick levelling compound for treating unevenness in layer thickness of 1 to 10 mm unextended, extended from 5 to 25 mm under textile flooring and elastic flooring indoors. For higher loads and as of 2 mm layer thickness suitable underneath parquets. Suitable for heavy loads of 3 mm layer thickness. Can be applied with a rakel. Can be pumped. Low in chromate according to REACH.

**Mixture:**  
approx. 5.75-6.0 l water + 25 kg Z 715

**Consumption:**  
approx. 1.6 kg/m<sup>2</sup>/mm application thickness

**Setting time:**  
suitable for walking after approx. 1-1.5 h; ready for laying up to 10 mm under PVC/CV flooring and linoleum after approx. 1.5 h, under parquet, rubber and cork after 12 h

**Pot life:**  
approx. 20 min.

**unextended:**  
1-10 mm

**extended:**  
5-25 mm

**Storage information:**  
store in a cool and dry place

**Base:**  
special cement

**CE marking:**  
EN 13813:2002 CT-C50-F10

**Order information:**  
507203 | 34910 – 25.0 kg – pallet: 42 pieces

WAKOL Z 610 Levelling Compound, dust-reduced



**Area of application:**  
Dust-reduced, low-tension, cement-based levelling compound for treating unevenness in layer thickness of 1 to 20 mm unextended, extended of 10 to 30 mm under textile flooring and elastic flooring indoors. For higher loads and as of 2 mm layer thickness suitable underneath parquets. Suitable for heavy loads of 3 mm layer thickness. Can be processed in combination with WAKOL D 3060 Plastification Additive. Can be applied with a rakel. Can be pumped. Suitable for direct use in conjunction with surface treatment. Low in chromate according to REACH.

**Mixture:**  
approx. 6.0-6.25 l water + 25 kg Z 610

**Consumption:**  
approx. 1.5 kg/m<sup>2</sup>/mm application thickness

**Setting time:**  
suitable for walking after approx. 2 h; ready for laying up to 5 mm after 6 h; up to 10 mm after 12 h; up to 20 mm after 24 h; up to 30 mm (extended) after 24 h

**Pot life:**  
approx. 20 min.

**unextended:**  
1-20 mm

**extended:**  
10-30 mm

**Storage information:**  
store in a cool and dry place

**Base:**  
special cement

**CE marking:**  
EN 13813:2002 CT-C35-F7

**Order information:**  
508112 | 38417 – 25.0 kg – pallet: 40 pieces

WAKOL Z 615 Levelling Compound, dust-reduced



**Area of application:**  
Cement-based levelling compound for treating unevenness in layer thickness of 1 to 10 mm unextended, extended of 10 to 30 mm under textile flooring and elastic flooring indoors. For higher loads and as of 2 mm layer thickness suitable underneath parquets. Suitable for heavy loads of 3 mm layer thickness. Can be processed in combination with WAKOL D 3060 Plastification Additive. Can be applied with a rakel. Can be pumped. Suitable for direct use in conjunction with surface treatment. Low in chromate according to REACH.

**Mixture:**  
approx. 6.25-6.5 l water + 25 kg Z 615

**Consumption:**  
approx. 1.5 kg/m<sup>2</sup>/mm application thickness

**Setting time:**  
suitable for walking after approx. 2 h; ready for laying up to 3 mm after 12 h; up to 5 mm after 24 h; up to 10 mm after 48 h; up to 15 mm after 72 h; up to 30 mm after 6 days

**Pot life:**  
approx. 20 min.

**unextended:**  
1-10 mm

**extended:**  
10-30 mm

**Storage information:**  
store in a cool and dry place

**Base:**  
special cement

**CE marking:**  
EN 13813:2002 CT-C35-F7

**Order information:**  
505908 | 34911 – 25.0 kg – pallet: 42 pieces

WAKOL Z 625 Levelling Compound



**Area of application:**  
Cement-based levelling compound for treating unevenness in layer thickness of 1 to 20 mm unextended, extended from 10 to 30 mm under textile flooring and elastic flooring indoors. For higher loads and as of 2 mm layer thickness suitable underneath parquets. Suitable for heavy loads of 3 mm layer thickness. Can be processed in combination with WAKOL D 3060 Plastification Additive. Can be applied with a rakel. Can be pumped. Suitable for direct use in conjunction with surface treatment. Low in chromate according to REACH.

**Mixture:**  
approx. 6.0-6.25 l water + 25 kg Z 625

**Consumption:**  
approx. 1.5 kg/m<sup>2</sup>/mm application thickness

**Setting time:**  
suitable for walking after approx. 2 h; ready for laying up to 5 mm after 6 h, up to 10 mm after 12 h, up to 30 mm after 24 h

**Pot life:**  
approx. 20 min.

**unextended:**  
1-20 mm

**extended:**  
10-30 mm

**Storage information:**  
store in a cool and dry place

**Base:**  
special cement

**CE marking:**  
EN 13813:2002 CT-C35-F7

**Order information:**  
506814 | 44986 – 25.0 kg – pallet: 40 pieces

WAKOL Z 630 Levelling Compound



**Area of application:**  
Self-levelling, cement-based levelling compound for treating unevenness in layer thicknesses of 1 to 15 mm unextended, extended from 10 to 25 mm under textile flooring and elastic flooring indoors. As of 2 mm layer thickness also underneath parquet. Can be processed in combination with WAKOL D 3060 Plastification Additive. Can be applied with a rakel. Can be pumped. Low in chromate according to REACH.

**Mixture:**  
approx. 6.25-6.5 l water + 25 kg Z 630

**Consumption:**  
approx. 1.5 kg/m<sup>2</sup>/mm application thickness

**Setting time:**  
suitable for walking after approx. 2h; ready for laying up to 3 mm after 6 h; up to 5 mm after 12 h; up to 10 mm after 24 h; up to 15 mm after 48 h; up to 25 mm extended after 48 h

**Pot life:**  
approx. 25 minutes

**unextended:**  
1-15 mm

**extended:**  
10-25 mm

**Storage information:**  
store in a cool and dry place

**Base:**  
special cement

**Blue Angel:**  
DE-UZ 113

**CE marking:**  
EN 13813: CT-C40-F7

**Order information:**  
506422 | 41665 – 25.0 kg – pallet: 42 pieces



WAKOL Z 635 Levelling Compound



**Area of application:**  
Cement-based levelling compound for treating unevenness in layer thicknesses of 1 to 10 mm under textile flooring and elastic flooring indoors. As of 2 mm layer thickness also underneath parquet. Can be applied with a rakel. Can be pumped. Low in chromate according to REACH.

**Mixture:**  
approx. 6.25 l water + 25 kg Z 635

**Consumption:**  
approx. 1.5 kg/m<sup>2</sup>/mm application thickness

**Setting time:**  
suitable for walking after approx. 2.5 h; ready for laying up to 5 mm after 24 h; up to 10 mm after 48 h

**Pot life:**  
approx. 25 min.

**unextended:**  
1 - 10 mm

**extended:**  
-

**Storage information:**  
store in a cool and dry place

**Base:**  
special cement

**Blue Angel:**  
DE-UZ 113

**CE marking:**  
EN 13813:2002 CT-C30-F7

**Order information:**  
508002 | 42286 – 25.0 kg – pallet: 40 pieces

WAKOL Z 640 Filling Compound



**Area of application:**  
Fine, stable, cement-based levelling compound for treating unevenness with layer thickness up to 20 mm unextended, extended from 10 to 50 mm, for smoothing steps and door joints as well as for repairing concrete subfloor damage indoors. Can be processed in combination with WAKOL D 3060 Plastification Additive. Flexible. Very good moldability. Low in chromate according to REACH.

**Mixture:**  
approx. 6.75-7.5 l water + 25 kg Z 640

**Consumption:**  
approx. 1.4 kg/m<sup>2</sup>/mm application thickness

**Setting time:**  
suitable for walking and coverable after approx. 30 min., ready for laying after approx. 3 h

**Pot life:**  
approx. 15 min.

**unextended:**  
up to 20 mm

**extended:**  
10 to 50 mm

**Storage information:**  
store in a cool and dry place

**Base:**  
special cement

**CE marking:**  
EN 13813:2002 CT-C35-F6

**Order information:**  
506512 | 32148 – 25.0 kg – pallet: 40 pieces

WAKOL Z 675 Levelling Compound



**Area of application:**  
Cement-based levelling compound for treating unevenness in layer thicknesses of 1 to 10 mm under textile flooring and elastic flooring indoors. Can be applied with a rakel. Can be pumped. Low in chromate according to REACH.

**Mixture:**  
approx. 6.0 l water + 25 kg Z 675

**Consumption:**  
approx. 1.5 kg/m<sup>2</sup>/mm application thickness

**Setting time:**  
suitable for walking after approx. 3 h; ready for laying up to 2 mm after 24 h; up to 5 mm after 48 h; up to 10 mm after 72 h

**Pot life:**  
approx. 30 min.

**unextended:**  
1-10 mm

**extended:**  
-

**Storage information:**  
store in a cool and dry place

**Base:**  
special cement

**CE marking:**  
EN 13813:2002 CT-C25-F6

**Order information:**  
506314 | 42287 – 25.0 kg – pallet: 40 pieces

WAKOL Z 645 Filling Compound, dust-reduced



**Area of application:**  
Dust-reduced, stable, cement-based levelling compound for treating unevenness in layer thicknesses of 1 to 10 mm unextended, extended from 10 to 50 mm for rough smoothing of uneven areas, smoothing steps and door joints and for repairing concrete subfloor damage indoors. Can be processed in combination with WAKOL D 3060 Plastification Additive. Flexible. Very good moldability. Low in chromate according to REACH.

**Mixture:**  
approx. 6.75-8.0 l water + 25 kg Z 645

**Consumption:**  
approx. 1.3 kg/m<sup>2</sup>/mm application thickness

**Setting time:**  
suitable for walking after approx. 30 min.; ready for laying after approx. 60 min.

**Pot life:**  
approx. 15 minutes

**unextended:**  
1-10 mm

**extended:**  
10-50 mm

**Storage information:**  
store in a cool and dry place

**Base:**  
special cement

**Blue Angel:**  
DE-UZ 113

**CE marking:**  
EN 13813: CT-C30-F7

**Order information:**  
506722 | 41371 – 25.0 kg – pallet: 40 pieces

WAKOL Z 680 Levelling Compound, dust-reduced



**Area of application:**  
Dust-reduced, cement-based levelling compound for treating unevenness in layer thicknesses of 1 to 10 mm under textile flooring and elastic flooring indoors. Can be applied with a rakel. Can be pumped. Low in chromate according to REACH.

**Mixture:**  
approx. 6.0 l water + 25 kg Z 680

**Consumption:**  
approx. 1.5 kg/m<sup>2</sup>/mm application thickness

**Setting time:**  
suitable for walking after approx. 3 h; ready for laying up to 3 mm after 24 h, up to 5 mm after 48 h, up to 10 mm after 72 h

**Pot life:**  
approx. 25 min.

**unextended:**  
1-10 mm

**extended:**  
-

**Storage information:**  
store in a cool and dry place

**Base:**  
special cement

**CE marking:**  
EN 13813:2002 CT-C25-F7

**Order information:**  
506912 | 38419 – 25.0 kg – pallet: 40 pieces

WAKOL A 830 Levelling Compound



**Area of application:**  
Levelling Compound based on calcium sulphate for treating unevenness in layer thicknesses of 1 to 20 mm unextended, extended of 10 to 30 mm under textile flooring and elastic flooring indoors; as of 2 mm layer thickness also underneath parquet. Can be processed in combination with WAKOL D 3060 Plastification Additive. Especially suitable on calcium sulphate bonded subfloors, dry extension elements, wooden material tiles and on cast asphalt concrete. Can be applied with a rakel. Can be pumped.

**Mixture:**  
approx. 6.0 l water + 25 kg A 830

**Consumption:**  
approx. 1.5 kg/m<sup>2</sup>/mm application thickness

**Setting time:**  
suitable for walking after 2 h; ready for laying up to 3 mm after 24h; 3-10 mm every mm 24 h drying time, ≥ 11 mm CM measurement (residual humidity < 0.5 CM%)

**Pot life:**  
approx. 25 min.

**unextended:**  
1-20 mm

**extended:**  
10-30 mm

**Storage information:**  
store in a cool and dry place

**Base:**  
calcium sulfate

**Blue Angel:**  
DE-UZ 113

**CE marking:**  
EN 13813:2002 CA-C30-F7

**Order information:**  
507703 | 35041 – 25.0 kg – pallet: 42 pieces

## WAKOL A 885 Levelling Compound

**Area of application:**

Levelling Compound based on calcium sulphate for treating unevenness in layer thicknesses of 1 to 20 mm unextended, extended of 10 to 30 mm under textile flooring and elastic flooring indoors. Especially suitable on calcium sulphate bonded subfloors, dry extension elements, wooden material tiles and on cast asphalt concrete. Can be applied with a rakel. Can be pumped.

**Mixture:**

approx. 5,25 - 5,5 l water + 25 kg WAKOL A 885

**Consumption:**

approx. 1.5 kg/m<sup>2</sup>/mm application thickness

**Setting time:**

suitable for walking after 3 h; ready for laying up to 3 mm after 24 h, 3-10 mm every mm 24 h drying time,  $\geq 11$  mm CM measurement (residual humidity < 0.5 CM%)

**Pot life:**

approx. 20 min.

**unextended:**

1-20 mm

**extended:**

10-30 mm

**Storage information:**

store in a cool and dry place

**Base:**

calcium sulfate

**CE marking:**

EN 13813:2002 CA-C25-F7

**Order information:**

507303 | 39219 – 25.0 kg – pallet: 40 pieces

## WAKOL A 850 Filling Compound

**Area of application:**

Fine, stable, fast drying calcium sulphate-based levelling compound for levelling unevenness in layer thicknesses of 0-20 mm unextended, up to 40 mm extended for smoothing out unevenness, levelling steps on stairways, adjusting door joints and repairing strongly damaged screeds indoors. Can be processed in combination with WAKOL D 3060 Plastification Additive.

**Mixture:**

approx. 5.0 l water + 20 kg A 850

**Consumption:**

approx. 1.4 kg/m<sup>2</sup>/mm application thickness

**Setting time:**

suitable for walking and coverable after approx. 30 min., ready for laying after approx. 4 h

**Pot life:**

approx. 15 min.

**unextended:**

0-20 mm

**extended:**

up to 40 mm

**Storage information:**

store in a cool and dry place

**Base:**

calcium sulfate

**CE marking:**

EN 13813:2002 CA-C30-F7

**Order information:**

505712 | 36004 – 20.0 kg – pallet: 42 pieces

## WAKOL Z 505 Repair Compound, fine

**Area of application:**

Cement-based repair compound for partial fine skimming, for treating unevennesses, for touching up subfloors, for smoothing steps and for patching door joints, for filling holes, depressions and cracks indoors. Low in chromate according to REACH.

**Mixture:**

approx. 0.33 l water + 1 kg Z 505

**Consumption:**

approx. 1.5 kg/m<sup>2</sup>/mm application thickness

**Setting time:**

suitable for walking and coverable after approx. 10 min., ready for laying after approx. 30 min., 12 h for laying parquet

**Pot life:**

approx. 5 min.

**unextended:**

0-70 mm

**extended:**

-

**Storage information:**

store in a cool and dry place, not sensitive to frost

**Base:**

special cement

**CE marking:**

EN 13813:2002 CT-C20-F7

**Order information:**

503804 | 22473 – 5.0 kg – pallet: 72 pieces

## WAKOL Z 515 Thin Screed

**Area of application:**

Quick-drying, self-levelling, cement-based thin screed, for treating unevenness in layer thicknesses between 3-30 mm unextended, 10-50 mm extended, under textile flooring and elastic flooring indoors. As of 2 mm layer thickness suitable underneath parquets. Can be pumped. Low in chromate according to REACH.

**Mixture:**

approx. 4.25 l water + 25 kg Z 515

**Consumption:**

approx. 1.7 kg/m<sup>2</sup>/mm application thickness

**Setting time:**

suitable for walking after approx. 2 h, ready for laying after 24 h

**Pot life:**

approx. 25 min.

**unextended:**

3-30 mm

**extended:**

10-50 mm

**Storage information:**

store in a cool and dry place

**Base:**

special cement

**CE marking:**

EN 13813:2002 CT-C35-F7

**Order information:**

505822 | 31486 – 25.0 kg – pallet: 40 pieces

## WAKOL Z 560 Rapid Screed

**Area of application:**

Fast-drying, low-tension quick cement screed for use in layer thicknesses between 20-60 mm for repairing and restoring flaws and imperfections, as well as for manufacturing compound screeds (from 20 mm), screeds on separating layers (from 35 mm) and screeds on insulation layers (from 35 mm) in internal areas. Can be pumped. Low in chromate according to REACH.

**Mixture:**

approx. 1.8 l water + 25 kg Z 560

**Consumption:**

approx. 1.85 kg/m<sup>2</sup>/mm application thickness

**Setting time:**

suitable for walking after approx. 3 h, coverable after approx. 3-4 h; ready for laying after 24 h

**Pot life:**

approx. 60 min.

**unextended:**

20-60 mm

**extended:**

-

**Storage information:**

store in a cool and dry place

**Base:**

special cement

**CE marking:**

EN 13813:2002 CT-C35-F6

**Order information:**

505102 | 31487 – 25.0 kg – pallet: 40 pieces

## WAKOL Z 590 Light Screed

**Area of application:**

Low-stress, cementitious lightweight screed for use in layer thicknesses of 20-300 mm in a system with WAKOL AR 150 Reinforcement Fabric and approved Wakol levelling compounds for levelling and filling substrates, even in structurally problematic areas with a bond (from 20 mm) and on a separating layer (from 30 mm) in internal areas. Can be pumped. Low in chromate according to REACH.

**Mixture:**

approx. 4.5-5.0 l water + 16 kg / 50 l Z 590

**Consumption:**

approx. 0.32 kg/m<sup>2</sup>/mm application thickness

**Setting time:**

suitable for walking after 12 h, ready for covering and can be levelled over after approx. 24 h

**Pot life:**

approx. 60 min.

**unextended:**

20-300 mm

**extended:**

-

**Storage information:**

store in a cool and dry place

**Base:**

polystyrene foam granules with cementitious binder

**Order information:**

505604 | 44918 – 16.0 kg | 50.0 l – pallet: 24 pieces



## WAKOL AR 114 Reinforcement Fibres



### Area of application:

Alkali-resistant glass fibres for reinforcing WAKOL Z 610 Levelling Compound, dust-reduced, WAKOL Z 615 Levelling Compound, dust-reduced, WAKOL Z 625 Levelling Compound, WAKOL Z 630 Levelling Compound and WAKOL A 830 Levelling Compound for reducing cracking on unstable subfloors, wood planks, wooden material tiles and prefabricated screeds indoors.

### Consumption:

1 bag per sac of levelling compound

### Storage information:

store in a cool and dry place, not sensitive to frost

### Base:

alkali-resistant glass fibres

### Order information:

595505 | 37262 – 15 bags with 0.25 kg each – pallet: 750 pieces; 50 buckets with 15 bags

## WAKOL EP 219 Screed Binder



### Area of application:

Two-component epoxy resin binder in a system with WAKOL S 25 Elongating Sand for the creation of epoxy resin screeds for reparation and renovation of screed defects, creation of bonded screeds (final screed thickness at least 15 mm), creation screeds on a separation layer or on an insulation layer (final screed thickness at least 25 mm) indoors.

### Mixture:

3.2 kg WAKOL EP 219 with 25 kg WAKOL S 25

### Consumption:

approx. 1.8 kg/m<sup>2</sup>/mm layer thickness mixed screed

### Setting time:

suitable for walking after 12 h, coverable/ready for laying after approx. 24 h

### Pot life:

approx. 60 min.

### Storage information:

store in a cool and dry place

### Base:

epoxy resins

### CE marking:

EN 13813:2002 SR-B2.0

### Order information:

3696/369702 | 45807 – 2.84 kg A + 0.36 kg B – pallet: 90 pieces

## WAKOL S 25 Elongating Sand



### Area of application:

Washed and dried quartz sand with grain size between 0.1 – 3.15 mm for elongation of approved Wakol levelling compounds, Wakol filling compounds, Wakol thin screed and for the creation of synthetic resin screed with WAKOL EP 219 Screed Binder.

### Mixture:

depending on the Wakol product to be elongated

### Storage information:

store in cool and dry place, not sensitive to frost

### Base:

quartz sand

### Order information:

506003 | 36005 – 25.0 kg – pallet: 40 pieces

## WAKOL S 28 Sprinkling Sand



### Area of application:

Washed and annealed sand with irregular, broken grain and a grain size of 0.2 to 0.8 mm for sprinkling reaction adhesives and reaction primers, as well as WAKOL PS 205 Cast Resin or WAKOL PS 275 Concrete Repair Primer.

### Application method:

by hand

### Consumption:

500-1000 g/m<sup>2</sup>

### Storage information:

store in cool and dry place, not sensitive to frost

### Base:

special sand

### Order information:

506103 | 34973 – 25.0 kg – pallet: 40 pieces

## BONDING ELASTIC FLOORING

## WAKOL MS 552 PVC and Rubber Adhesive



### Area of application:

Structure viscous 1-component MS adhesive for laying LVT flooring, homogeneous and heterogeneous PVC flooring, CV flooring, rubber flooring, needle fleece flooring, linoleum flooring, PVC cork flooring according to DIN EN 655, entrance mats, artificial lawn and Wakol Sealing systems on absorbent and non-absorbent wall and floor areas indoors. Waterproof. WAKOL MS 552 corresponds to DIN EN ISO 22636.

### Application method:

trowel notch size according to TKB A1, A2, B1 or B2

### Consumption:

approx. 300-580 g/m<sup>2</sup>

### Airing time:

approx. 5-30 minutes

### Open time:

approx. 10-35 minutes

### Storage information:

not sensitive to frost

### Base:

MS polymer

### Order information:

363905 | 35276 – 7.5 kg – pallet: 72 pieces

## WAKOL MS 550 PVC and Rubber Adhesive



### Area of application:

1-component MS adhesive for laying homogeneous and heterogeneous PVC flooring in planks and tiles, LVT flooring, CV flooring, needle fleece flooring, linoleum flooring, PVC cork flooring, entrance mats, artificial lawn as well as caoutchouc flooring in planks and tiles on absorbent and non-absorbent subfloors indoors and outdoors. Waterproof. WAKOL MS 550 corresponds to DIN EN ISO 22636.

### Application method:

trowel notch size according to TKB A1, A2, B1 or B2

### Consumption:

approx. 300-580 g/m<sup>2</sup>

### Airing time:

approx. 5-30 minutes

### Open time:

approx. 10-35 minutes

### Storage information:

not sensitive to frost

### Base:

MS polymer

### Order information:

363805 | 35279 – 7.5 kg – pallet: 72 pieces



## WAKOL PU 270 Polyurethane Adhesive



### Area of application:

2-component polyurethane adhesive for laying caoutchouc flooring with smooth and profiled backing, linoleum flooring, textile flooring, outdoor flooring and PVC flooring on absorbent and non-absorbent subfloors indoors and outdoors. Waterproof. WAKOL PU 270 corresponds to DIN EN ISO 22636.

### Application method:

trowel notch size according to TKB A2, B1 or B2

### Consumption:

approx. 350-700 g/m<sup>2</sup>

### Airing time:

approx. 5-70 minutes, depending on type of floor covering

### Open time:

approx. 70-80 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

polyurethane resin

### Order information:

369206 + 369306 | 41280 – combination pack  
6.0 kg A-comp. + 1.05 kg B-comp. – pallet: 60 pieces



## WAKOL DL 3365 StarLeit



### Area of application:

Light-coloured, fibre-containing dispersion adhesive for the laying of conductive PVC, textile and linoleum flooring as well as for conductive caoutchouc flooring of thickness up to 4 mm on appropriately prepared subfloors. WAKOL DL 3365 corresponds to DIN EN ISO 22636.

### Application method:

trowel notch size according to TKB S2, Pajarito 7 or Pajarito 25; trowel notch enclosed

### Consumption:

approx. 250-550 g/m<sup>2</sup>

### Airing time:

approx. 10-15 minutes

### Open time:

approx. 20-40 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

acrylate dispersion

### Order information:

336504 | 30098 – 12.0 kg – pallet: 40 pieces



## WAKOL D 3360 VersaTack



### Area of application:

Dispersion adhesive for laying LVT flooring, linoleum, caoutchouc flooring up to 2.5 mm layer thickness, textile flooring with fleece backing, latex foam backing, synthetic double backing or jute backing, woven textile flooring and needle fleece flooring on absorbent subfloors as well as for PVC and CV flooring on absorbent and non-absorbent subfloors. WAKOL D 3360 corresponds to DIN EN ISO 22636.

### Application method:

trowel notch size according to TKB A1, A2, B1 or B2

### Consumption:

approx. 250-550 g/m<sup>2</sup>

### Airing time:

approx. 10-20 minutes

### Open time:

approx. 20-30 minutes

### Storage information:

not below +5°C, sensitive to frost

### Base:

acrylate dispersion

### Order information:

336002 | 25689 – 14.0 kg – pallet: 44 pieces  
336004 | 35847 – 6.0 kg – pallet: 90 pieces



## WAKOL D 3330 LVT Flooring Adhesive



### Area of application:

Dispersion adhesive for laying approved LVT flooring in tiles and planks up to a max. lengths of 125 cm and flat-lying heterogeneous PVC or CV flooring in rolls on subfloors levelled with cement-based Wakol levelling compound and primed with WAKOL D 3004 Primer Concentrate, diluted with water, or WAKOL D 3003 Dispersion Primer. Also suitable for laying modular textile floor coverings (without multiple restarts), using the contact method, WAKOL D 3330 LVT Flooring Adhesive is also suitable for laying PVC soft skirting and in stair areas, for PVC flooring on steps and risers.

### Application method:

special roller, enclosed

### Consumption:

approx. 120-140 g/m<sup>2</sup>

### Airing time:

approx. 20-30 minutes

### Open time:

approx. 180 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

acrylate dispersion

### Order information:

333004 | 37451 – 10.0 kg – pallet: 24 pieces



## WAKOL D 3320 PVC Adhesive



### Area of application:

Dispersion adhesive for laying LVT flooring, homogeneous caoutchouc flooring up to 2.5 mm layer thickness, heterogeneous caoutchouc flooring up to 4 mm layer thickness, textile flooring with PVC, PUR or latex fittings on absorbent subfloors, homogeneous PVC flooring in sheets and tiles and CV flooring on all absorbent and non-absorbent subfloors indoors. WAKOL D 3320 corresponds to DIN EN ISO 22636.

### Application method:

trowel notch size according to TKB A1, A2 or B1

### Consumption:

approx. 250-450 g/m<sup>2</sup>

### Airing time:

approx. 5-20 minutes on absorbent subfloors, approx. 30-40 minutes on non-absorbent subfloors

### Open time:

approx. 30-50 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

acrylate dispersion

### Order information:

332003 | 25253 – 12.0 kg – pallet: 44 pieces



## WAKOL D 3319 LVT Flooring Adhesive, fibre-containing



### Area of application:

Fibre-reinforced, dispersion-based wet-bed adhesive for laying LVT flooring in planks and tiles, homogeneous and heterogeneous PVC flooring in planks and tiles as well as CV flooring on absorbent subfloors indoors. WAKOL D 3319 corresponds to DIN EN ISO 22636.

### Application method:

trowel notch size according to TKB A2

### Consumption:

approx. 250-300 g/m<sup>2</sup>

### Airing time:

approx. 5-10 minutes

### Open time:

approx. 10-20 minutes

### Storage information:

not below +5 °C; sensitive to frost

### Base:

acrylate dispersion

### Order information:

331902 | 32408 – 13.0 kg – pallet: 44 pieces



## WAKOL D 3318 MultiFlex, fibre-containing



### Area of application:

Fibre-reinforced, dispersion adhesive for laying homogeneous and heterogeneous PVC flooring in strips and tiles, LVT flooring adhesive in planks and tiles, PVC-free floor coverings with PU or PO base or with fleece backing in strips, boards and tiles, CV Flooring, linoleum flooring and rubber flooring up to a thickness of 4 mm on properly prepared absorbent subfloors indoors. WAKOL D 3318 corresponds to DIN EN ISO 22636.

### Application method:

trowel notch size according to TKB A2 or B1

### Consumption:

approx. 290-350 g/m<sup>2</sup>

### Airing time:

approx. 5-15 minutes

### Open time:

approx. 30 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

acrylate dispersion

### Blue Angel:

DE-UZ 113

### Order information:

331803 | 35855 – 13.0 kg – pallet: 44 pieces  
331805 | 35854 – 6.0 kg – pallet: 90 pieces

## WAKOL D 3313 PVC free Adhesive



### Area of application:

Dispersion-based adhesive for laying PVC-free flooring with PU or PO base or with fleece backing in strips, boards and tiles, homogeneous and heterogeneous PVC flooring in strips and tiles, LVT flooring in planks and tiles, CV flooring as well as caoutchouc flooring up to 4 mm layer thickness on absorbent subfloors indoors. WAKOL D 3313 corresponds to DIN EN ISO 22636.

### Application method:

trowel notch size according to TKB A2 or B1

### Consumption:

approx. 280-420 g/m<sup>2</sup>

### Airing time:

approx. 5-10 minutes

### Open time:

approx. 25 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

polymer dispersion

### Blue Angel:

DE-UZ 113

### Order information:

331305 | 36075 – 12.0 kg – pallet: 44 pieces

## WAKOL D 3317 PVC Adhesive, fibre-containing



### Area of application:

Fibre-reinforced dispersion based adhesive for laying LVT flooring in planks and tiles, homogeneous and heterogeneous PVC flooring in rolls and tiles, CV flooring as well as caoutchouc flooring up to 2.5 mm layer thickness on absorbent subfloors indoors. WAKOL D 3317 corresponds to DIN EN ISO 22636.

### Application method:

trowel notch size according to TKB A2

### Consumption:

approx. 300-330 g/m<sup>2</sup>

### Airing time:

approx. 5-15 minutes

### Open time:

approx. 10-25 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

acrylate dispersion

### Order information:

331703 | 44526 – 13.0 kg – pallet: 44 pieces

## WAKOL D 3307 PVC Adhesive



### Area of application:

Dispersion adhesive for laying homogeneous and heterogeneous PVC flooring in planks and tiles, LVT flooring, CV flooring, textile flooring with fleece backing, textile double backing or jute backing as well as woven textile flooring on absorbent subfloors indoors. WAKOL D 3307 corresponds to DIN EN ISO 22636.

### Application method:

trowel notch size according to TKB A2, B1 or B2

### Consumption:

approx. 330-530 g/m<sup>2</sup>

### Airing time:

approx. 10-20 minutes

### Open time:

approx. 15-20 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

acrylate dispersion

### Blue Angel:

DE-UZ 113

### Order information:

330703 | 35867 – 14.0 kg – pallet: 44 pieces  
330705 | 35863 – 6.0 kg – pallet: 90 pieces  
330706 | 35865 – 3.0 kg – pallet: 150 pieces

## WAKOL D 3316 PVC Adhesive, fibre-containing



### Area of application:

Fibre-reinforced dispersion based adhesive for laying LVT flooring in planks and tiles, homogeneous and heterogeneous PVC flooring in rolls and tiles as well as CV flooring on absorbent subfloors indoors. WAKOL D 3316 corresponds to DIN EN ISO 22636.

### Application method:

trowel notch size according to TKB A2

### Consumption:

approx. 300-330 g/m<sup>2</sup>

### Airing time:

approx. 5-10 minutes

### Open time:

approx. 10-15 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

acrylate dispersion

### Blue Angel:

DE-UZ 113

### Order information:

331607 | 44433 – 13.0 kg – pallet: 44 pieces

## WAKOL D 3125 LVT Flooring Adhesive



### Area of application:

Dispersion based adhesive for laying LVT flooring, homogeneous and heterogeneous PVC flooring in planks and tiles, CV flooring on absorbent and non-absorbent subfloors. WAKOL D 3125 corresponds to DIN EN ISO 22636.

### Application method:

trowel notch size according to TKB A1

### Consumption:

approx. 190-220 g/m<sup>2</sup> with TKB A1

### Airing time:

approx. 30 minutes on absorbent subfloors, approx. 60 minutes on non-absorbent subfloors

### Open time:

approx. 180 minutes

### Storage information:

not below +5 °C; sensitive to frost

### Base:

acrylate dispersion

### Order information:

312503 | 35885 – 10.0 kg – pallet: 44 pieces



## WAKOL MS 246 StarMonti



**Area of application:**  
Firm-elastic 1-component MS mounting adhesive for bonding skirtings made of wood or plastic, wooden materials and metals on absorbent and non-absorbent subfloors indoors. Can be painted over.

**Application method:**  
WAKOL Manual Applicator 400 or WAKOL Applicator 50 with enclosed nozzle

**Airing time:**  
none

**Open time:**  
approx. 5-10 minutes

**Hardening time:**  
up to 2.5 mm layer after 24 hours

**Storage information:**  
store in a cool and dry place, not sensitive to frost

**Base:**  
MS polymer

**Order information:**  
362603 | 36179 – 310 ml – pallet: 1.152 pieces; 96 boxes with 12 pieces

## WAKOL MS 245 Montinator



**Area of application:**  
Solvent-free, single-component, elastic MS mounting adhesive for bonding wood materials, metals, plastics, concrete, stone, decorative sheets, wall panelling, panels and wood borders. Can be painted over.

**Application method:**  
WAKOL Manual Applicator 400 or WAKOL Applicator 50 with enclosed nozzle

**Airing time:**  
none

**Open time:**  
approx. 5-10 minutes

**Hardening time:**  
up to 2.5 mm layer after 24 hours

**Temperature resistant:**  
-40 °C to +90 °C

**Storage information:**  
store in a cool and dry place, not sensitive to frost

**Base:**  
MS polymer

**Order information:**  
362505 | 35000 – 310 ml – pallet: 1.152 pieces; 96 boxes with 12 pieces

## WAKOL L 1940 Spray Adhesive



**Area of application:**  
Solvent-based, spray contact adhesive to install textile flooring such as tufting, woven flooring and needle fleece flooring on stairs, linoleum flooring, rubber flooring as well as skirtings free of plasticising substances on properly prepared absorbent and non-absorbent subfloors indoors.

**Application method:**  
spray on both sides in a thin layer

**Consumption:**  
approx. 160-180 ml/m² for double-sided application

**Airing time:**  
1-2 minutes

**Open time:**  
4 hours

**Storage information:**  
not below +10°C and not more than +50°C

**Base:**  
synthetic rubber

**Order information:**  
194010 | 46476 – 500 ml – 1 box with 12 pieces each

## WAKOL NE 479 Contact Adhesive



**Area of application:**  
Neoprene adhesive for laying skirting boards as well as textile, homogeneous PVC, caoutchouc, natural cork and linoleum flooring on stairs on absorbent and non-absorbent subfloors.

**Application method:**  
on both sides with brush, smooth spatula or trowel notch size according to TKB A1

**Consumption:**  
approx. 200-300 g/m²

**Airing time:**  
approx. 15 minutes

**Open time:**  
approx. 50 minutes

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
polychloroprene

**Order information:**  
147926 | 35269 – 6.0 kg – pallet: 60 pieces  
147924 | 35270 – 0.65 kg – pallet: 500 pieces; 50 boxes with 10 pieces

## WAKOL NE 470 Contact Adhesive



**Area of application:**  
Neoprene adhesive for laying skirting boards, edges of staircases and laying staircases with textile flooring, homogeneous PVC coverings, rubber floor coverings, linoleum flooring, natural cork coverings on absorbent and non-absorbent subfloors indoors.

**Application method:**  
both sides with brush, both sides with smooth spatula or trowel notch size according to TKB A1

**Consumption:**  
approx. 200-350 g/m²

**Airing time:**  
approx. 15-20 minutes

**Open time:**  
approx. 30 minutes

**Storage information:**  
not below +5 °C; sensitive to frost

**Base:**  
polychloroprene

**Order information:**  
147007 | 35271 – 6.0 kg – pallet: 60 pieces

### BONDING LINOLEUM / TEXTILE FLOORING

## WAKOL DL 3365 StarLeit



**Area of application:**  
Light-coloured, fibre-containing dispersion adhesive for the laying of conductive PVC, textile and linoleum flooring as well as for conductive caoutchouc flooring of thickness up to 4 mm on appropriately prepared subfloors. WAKOL DL 3365 corresponds to DIN EN ISO 22636.

**Application method:**  
trowel notch size according to TKB S2, Pajarito 7 or Pajarito 25; trowel notch enclosed

**Consumption:**  
approx. 250-550 g/m²

**Airing time:**  
approx. 10-15 minutes

**Open time:**  
approx. 20-40 minutes

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
acrylate dispersion

**Order information:**  
336504 | 30098 – 12.0 kg – pallet: 40 pieces

## WAKOL D 3360 VersaTack


**Area of application:**

Dispersion adhesive for laying LVT flooring, linoleum, caoutchouc flooring up to 2.5 mm layer thickness, textile flooring with fleece backing, latex foam backing, synthetic double backing or jute backing, woven textile flooring and needle fleece flooring on absorbent subfloors as well as for PVC and CV flooring on absorbent and non-absorbent subfloors. WAKOL D 3360 corresponds to DIN EN ISO 22636.

**Application method:**

trowel notch size according to TKB A1, A2, B1 or B2

**Consumption:**

approx. 250-550 g/m<sup>2</sup>

**Airing time:**

approx. 10-20 minutes

**Open time:**

approx. 20-30 minutes

**Storage information:**

not below +5°C, sensitive to frost

**Base:**

acrylate dispersion

**Order information:**

336002 | 25689 – 14.0 kg – pallet: 44 pieces  
336004 | 35847 – 6.0 kg – pallet: 90 pieces



## WAKOL D 3318 MultiFlex, fibre-containing


**Area of application:**

Fibre-reinforced, dispersion adhesive for laying homogeneous and heterogeneous PVC flooring in strips and tiles, LVT flooring adhesive in planks and tiles, PVC-free floor coverings with PU or PO base or with fleece backing in strips, boards and tiles, CV Flooring, linoleum flooring and rubber flooring up to a thickness of 4 mm on properly prepared absorbent subfloors indoors. WAKOL D 3318 corresponds to DIN EN ISO 22636.

**Application method:**

trowel notch size according to TKB A2 or B1

**Consumption:**

approx. 290-350 g/m<sup>2</sup>

**Airing time:**

approx. 5-15 minutes

**Open time:**

approx. 30 minutes

**Storage information:**

not below +5 °C, sensitive to frost

**Base:**

acrylate dispersion

**Blue Angel:**

DE-UZ 113

**Order information:**

331803 | 35855 – 13.0 kg – pallet: 44 pieces  
331805 | 35854 – 6.0 kg – pallet: 90 pieces



## WAKOL D 3312 Carpet Adhesive


**Area of application:**

High shear-resistant dispersion adhesive for laying needle fleece flooring, textile flooring with fleece, synthetic double or jute backing as well as woven flooring on absorbent subfloors. WAKOL D 3312 corresponds to DIN EN ISO 22636.

**Application method:**

trowel notch size according to TKB B1 or B2

**Consumption:**

approx. 400-525 g/m<sup>2</sup>

**Airing time:**

approx. 5-15 minutes

**Open time:**

approx. 15 minutes

**Storage information:**

not below +5 °C; sensitive to frost

**Base:**

acrylate dispersion

**Order information:**

331203 | 35858 – 14.0 kg – pallet: 44 pieces



## WAKOL D 3311 Linoleum and Carpet Adhesive


**Area of application:**

Dispersion adhesive for laying linoleum flooring, korkment flooring, tufting flooring with matted backing, synthetic second backing or jute backing, woven flooring and needle fleece flooring on absorbent subfloors indoors. WAKOL D 3311 corresponds to DIN EN ISO 22636.

**Application method:**

trowel notch size according to TKB B1 or B2

**Consumption:**

approx. 325-450 g/m<sup>2</sup>

**Airing time:**

approx. 0-10 minutes

**Open time:**

approx. 15 minutes

**Storage information:**

not below +5 °C; sensitive to frost

**Base:**

acrylate dispersion

**Blue Angel:**

DE-UZ 113

**Order information:**

331102 | 35859 – 14.0 kg – pallet: 44 pieces



## WAKOL D 3310 Carpet Adhesive, low-odour


**Area of application:**

Dispersion adhesive for laying textile flooring with fleece backing, synthetic double backing or jute backing, woven flooring and needle fleece flooring on absorbent subfloors. Odour-neutral after coat is fully dry. WAKOL D 3310 corresponds to DIN EN ISO 22636.

**Application method:**

trowel notch size according to TKB B1 or B2

**Consumption:**

approx. 400-525 g/m<sup>2</sup>

**Airing time:**

approx. 5-10 minutes

**Open time:**

approx. 10-15 minutes

**Storage information:**

not below +5 °C, sensitive to frost

**Base:**

acrylate dispersion

**Blue Angel:**

DE-UZ 113

**Order information:**

331002 | 35860 – 14.0 kg – pallet: 44 pieces



## WAKOL D 3308 Carpet Adhesive


**Area of application:**

Dispersion adhesive for laying textile flooring with fleece backing, synthetic double backing or jute backing, woven flooring, needle fleece flooring and PVC/CV flooring with fleece backing on absorbent subfloors. WAKOL D 3308 corresponds to DIN EN ISO 22636.

**Application method:**

trowel notch size according to TKB A2, B1 or B2

**Consumption:**

approx. 300-525 g/m<sup>2</sup>

**Airing time:**

approx. 5-10 minutes

**Open time:**

approx. 10-15 minutes

**Storage information:**

not below +5 °C, sensitive to frost

**Base:**

acrylate dispersion

**Order information:**

330809 | 46214 – 12.0 kg – pallet: 44 pieces





## WAKOL D 3304 Linoleum Adhesive



### Area of application:

Dispersion adhesive for laying linoleum and cork flooring, tufting flooring with fleece, synthetic double or jute backing as well as woven flooring and needle fleece flooring on absorbent subfloors. WAKOL D 3304 corresponds to DIN EN ISO 22636.

### Application method:

trowel notch size according to TKB B1 or B2

### Consumption:

approx. 375-500 g/m²

### Airing time:

approx. 0-5 minutes

### Open time:

approx. 15 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

acrylate dispersion

### Blue Angel:

DE-UZ 113

### Order information:

330404 | 35870 – 14.0 kg – pallet: 44 pieces



## WAKOL D 3270 SpaltTex



### Area of application:

Dispersion-based adhesive for renovation with "built-in zipper" for laying textile flooring with fleece backing or synthetic double backing or Fabromont twined yarn® on absorbent subfloors. Flooring can be easily removed without residue. WAKOL D 3270 corresponds to DIN EN ISO 22636.

### Application method:

trowel notch size according to TKB B1 or B2

### Consumption:

approx. 250-400 g/m²

### Airing time:

approx. 5-10 minutes

### Open time:

approx. 15 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

acrylate dispersion

### Order information:

327002 | 35872 – 10.0 kg – pallet: 44 pieces



## WAKOL PU 272 Artificial Turf Adhesive



### Area of application:

2-component, green coloured PU adhesive for laying artificial turf on WAKOL AS 130 Seaming Tape, on absorbent and non-absorbent subfloors as well as moist, but superficially dried, drainable subfloors outdoors.

### Application method:

trowel notch size according to TKB B3 or B11

### Consumption:

approx. 850-1200 g/m²

### Airing time:

none

### Open time:

approx. 90 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

polyurethane resin

### Order information:

368812 | 41343 – 12.0 kg A-comp. – pallet: 44 pieces  
369412 | 41344 – 1.12 kg B-Comp. – pallet: 440 pieces;  
40 boxes with 11 pieces



## WAKOL MS 299 Parquet Adhesive, shear-resistant



### Area of application:

Shear-resistant, 1-component MS parquet adhesive for laying mosaic, on-edge lamella, strip, 10 mm solid wood lam and multi-layer parquet, solid planks, wood block RE/WE as well as cork flooring with HDF/MDF middle layer with tongue and groove resp. click-connection on absorbent and non-absorbent subfloors indoors. WAKOL MS 299 is free from plasticizing substances. WAKOL MS 299 corresponds to DIN EN ISO 17178.

### Application method:

trowel notch size according to TKB B3, B11, B13 or B15

### Consumption:

approx. 800-1500 g/m²

### Airing time:

none

### Open time:

approx. 40 minutes

### Storage information:

store in a cool and dry place, not sensitive to frost

### Base:

MS polymer

### Blue Angel:

DE-UZ 113

### Order information:

362308 | 42148 – 18.0 kg sealed – pallet: 44 pieces



## WAKOL MS 292 Parquet Adhesive, shear-resistant



### Area of application:

Shear-resistant, structure viscous 1-component MS parquet adhesive for the laying of mosaic, on-edge lamella, 10 mm solid wood lam parquet, strip, multi-layer parquet, solid wood planks as well as cork flooring with HDF/MDF middle layer with tongue and groove resp. click-connection on absorbent and non-absorbent subfloors indoors. WAKOL MS 292 is free from plasticizing substances. WAKOL MS 292 corresponds to DIN EN ISO 17178.

### Application method:

trowel notch size according to TKB B3, B11, B13 or B15, WAKOL Applicator 90 and WAKOL Replaceable Nozzle

### Consumption:

approx. 550-725 ml/m² with WAKOL Replaceable Nozzle,  
approx. 500-950 ml/m² with WAKOL Parquet Notched Trowel

### Airing time:

none

### Open time:

approx. 40 minutes

### Storage information:

store in a cool and dry place; not sensitive to frost

### Base:

MS-Polymer

### Order information:

363403 | 35288 – 4.200 ml (Ø88 mm) – pallet: 108 pieces;  
54 boxes with 2 pieces



## WAKOL MS 290 Parquet Adhesive, shear-resistant



### Area of application:

1-component MS parquet adhesive for the shear-resistant laying of mosaic, on-edge lamella, 10 mm solid wood lam parquet, strip, multi-layer parquet, solid planks, wood block RE/WE as well as flat-lying cork flooring and cork flooring with HDF/MDF middle layer with tongue and groove resp. click-connection on absorbent and non-absorbent subfloors indoors. WAKOL MS 290 is free from plasticizing substances. WAKOL MS 290 corresponds to DIN EN ISO 17178.

### Application method:

trowel notch size according to TKB B3, B11, B13, B15 (parquet), A2 (cork)

### Consumption:

approx. 400-450 g/m² cork approx. 800-1500 g/m² parquet

### Airing time:

none

### Open time:

approx. 40 minutes

### Storage information:

store in a cool and dry place, not sensitive to frost

### Base:

MS polymer

### Order information:

363707 | 35290 – 18.0 kg sealed – pallet: 44 pieces



## WAKOL MS 265 Parquet Adhesive, firm-elastic



### Area of application:

Firm-elastic 1-component MS parquet adhesive for laying mosaic, on-edge lamella (min. 16 mm in width, max. 200 mm in length), strip, 10 mm solid wood lam and multi-layer parquet, solid planks (up to max. 18 cm in width, type of wood oak up to max. 20 cm in width), wood block RE/WE as well as flatlying cork flooring and cork flooring with HDF/MDF middle layer with tongue and groove resp. click-connection on absorbent and non-absorbent subfloors indoors. WAKOL MS 265 is free from plasticizing substances. WAKOL MS 265 corresponds to DIN EN ISO 17178.

### Application method:

trowel notch size according to TKB B3, B11, B13 or B15 (parquet), A2 (cork)

### Consumption:

approx. 700-1500 g/m<sup>2</sup> parquet, approx. 400-450 g/m<sup>2</sup> cork

### Airing time:

none

### Open time:

approx. 40 minutes

### Storage information:

store in a cool and dry place, not sensitive to frosts

### Base:

MS polymer

### Order information:

362203 | 36165 – 18.0 kg sealed – pallet: 44 pieces

## WAKOL MS 260 Parquet Adhesive, firm-elastic



### Area of application:

Firm-elastic 1-component MS parquet adhesive for laying mosaic, on-edge lamella (min. 16 mm in width, max. 200 mm in length), strip, 10 mm solid wood lam parquet, multi-layer parquet, solid planks (up to max. 18 cm in width, type of wood oak up to max. 20 cm in width), wood block RE/WE as well as flatlying cork flooring and cork flooring with HDF/MDF middle layer with tongue and groove resp. click-connection on absorbent and non-absorbent subfloors indoors. WAKOL MS 260 corresponds to DIN EN ISO 17178.

### Application method:

trowel notch size according to TKB B3, B11, B13 or B15 (parquet), A2 (cork), WAKOL Speciality Trowel 5, WAKOL Speciality Trowel Blade 5

### Consumption:

approx. 700-1500 g/m<sup>2</sup> parquet approx. 400-450 g/m<sup>2</sup> cork  
approx. 1700-1800 g/m<sup>2</sup> with WAKOL Speciality Trowel 5 or WAKOL Speciality Trowel Blade 5

### Airing time:

none

### Open time:

approx. 40 minutes

### Storage information:

store in a cool and dry place, not sensitive to frost

### Base:

MS polymer

### Order information:

362007 | 41338 – 18.0 kg sealed – pallet: 44 pieces

## WAKOL MS 262 Parquet Adhesive, firm-elastic



### Area of application:

Firm-elastic, structure viscous 1-component MS parquet adhesive for laying mosaic, on-edge lamella (min. 16 mm thick, max. 200 mm long), strip, multi-layer parquet, solid wood planks (up to 18 cm in width, oak up to 20 cm wide) as well as cork flooring with HDF/MDF middle layer with tongue and groove resp. click-connection on absorbent and non-absorbent wall and floor areas indoors. WAKOL MS 262 corresponds to DIN EN ISO 17178.

### Application method:

trowel notch size according to TKB B3, B11, B13 or B15, tubular bag gun, e.g. WAKOL Applicator 90 or 50 and special application nozzle or WAKOL Replaceable Nozzles

### Consumption:

approx. 450-500 ml/m<sup>2</sup> combining WAKOL TS 160/TS 170;  
approx. 600-800 ml/m<sup>2</sup> strip application, approx. 500-950 ml/m<sup>2</sup> with WAKOL Parquet Notched Trowel; approx. 425-850 ml/m<sup>2</sup> WAKOL Replaceable Nozzles

### Airing time:

none

### Open time:

approx. 40 minutes

### Storage information:

store in a cool and dry place; not sensitive to frost

### Base:

MS-Polymer

### Order information:

363207 | 30111 – 600 ml (Ø49 mm) – pallet: 864 pieces;  
72 boxes with 12 pieces  
363206 | 30112 – 1.800 ml (Ø62 mm) – pallet: 216 pieces;  
36 boxes with 6 pieces  
363205 | 32219 – 4.200 ml (Ø88 mm) – pallet: 108 pieces;  
54 boxes with 2 pieces  
363210 | 35296 – 18.0 kg sealed – pallet: 44 pieces

## WAKOL MS 258 Parquet Adhesive, firm-elastic



### Area of application:

Firm-elastic 1-component MS parquet adhesive for laying mosaic, on-edge lamella (min. 16 mm in width, max. 200 mm in length), strip and multi-layer parquet, solid planks (up to max. 18 cm in width), as well as cork flooring with HDF/MDF middle layer with tongue and groove resp. click-connection on absorbent and non-absorbent subfloors indoors. WAKOL MS 258 corresponds to DIN EN ISO 17178.

### Application method:

trowel notch size according to TKB B3, B11, B13 or B15, WAKOL Speciality Trowel 5, WAKOL Speciality Trowel Blade 5

### Consumption:

approx. 800-1500 g/m<sup>2</sup> parquet, approx. 1700-1800 g/m<sup>2</sup> with WAKOL Speciality Trowel 5 or WAKOL Speciality Trowel Blade 5

### Airing time:

none

### Open time:

approx. 40 minutes

### Storage information:

store in a cool and dry place, not sensitive to frost

### Base:

MS polymer

### Order information:

365802 | 46429 – 18,0 kg sealed – pallet: 44 pieces

## WAKOL MS 261 Parquet Adhesive, firm-elastic



### Area of application:

Firm-elastic 1-component MS parquet adhesive for laying mosaic, on-edge lamella (min. 16 mm in width, max. 200 mm in length), strip, 10 mm solid wood lam and multi-layer parquet, solid planks (up to max. 18 cm in width, type of wood oak up to max. 20 cm in width), wood block RE/WE as well as cork flooring with HDF/MDF middle layer with tongue and groove resp. click-connection on absorbent and non-absorbent subfloors indoors. WAKOL MS 261 corresponds to DIN EN ISO 17178.

### Application method:

trowel notch size according to TKB B3, B11, B13 or B15, WAKOL Speciality Trowel 5 or WAKOL Speciality Trowel Blade 5

### Consumption:

approx. 700-1500 g/m<sup>2</sup>; approx. 1700-1800 g/m<sup>2</sup> with WAKOL Speciality Trowel 5 or WAKOL Speciality Trowel Blade 5

### Airing time:

none

### Open time:

approx. 90 minutes

### Storage information:

store in a cool and dry place, not sensitive to frost

### Base:

MS polymer

### Order information:

362407 | 35298 – 18.0 kg sealed – pallet: 44 pieces

## WAKOL MS 239 Parquet Adhesive, elastic



### Area of application:

Elastic 1-component MS parquet adhesive for laying mosaic, on-edge lamella parquet (min. 16 mm in width, max. 200 mm in length), strip flooring parquet (max. 80 mm in width, max. 600 mm in length), as well as multi-layered parquet on absorbent and non-absorbent subfloors indoors. WAKOL MS 239 corresponds to DIN EN ISO 17178.

### Application method:

trowel notch size according to TKB B3, B11, B13 or B15, WAKOL Speciality Trowel 5 or WAKOL Speciality Trowel Blade 5

### Consumption:

approx. 800-1500 g/m<sup>2</sup> parquet, approx. 1700-1800 g/m<sup>2</sup> with WAKOL Speciality Trowel 5 or WAKOL Speciality Trowel Blade 5

### Airing time:

none

### Open time:

approx. 40 minutes

### Storage information:

store in a cool and dry place, not sensitive to frost

### Base:

MS polymer

### Blue Angel:

DE-UZ 113

### Order information:

362702 | 46428 – 18,0 kg sealed – pallet: 44 pieces



WAKOL MS 232 Parquet Adhesive, elastic



**Area of application:**  
Elastic, structure viscous 1-component MS parquet adhesive for laying of on-edge lamella parquet (min. 22 mm thick, max. 200 mm long), strip parquet (22 mm, type of wook oak) and multi-layer parquet on absorbent and non-absorbent subfloors indoors. WAKOL MS 232 corresponds to DIN EN ISO 17178.

**Application method:**  
trowel notch size according to TKB B3, B11, B13 or B15, WAKOL Applicator 90 and WAKOL Replaceable Nozzle

**Consumption:**  
approx. 550-725 ml/m² with WAKOL Replaceable Nozzle, approx. 500-800 ml/m² with WAKOL Parquet Notched Trowel

**Airing time:**  
none

**Open time:**  
approx. 40 minutes

**Storage information:**  
store in a cool and dry place, not sensitive to frost

**Base:**  
MS-Polymer

**Order information:**  
363303 | 35303 – 4.200 ml (Ø88 mm) – pallet: 108 pieces;  
54 pieces with 2 pieces  
363304 | 35304 – 1.800 ml (Ø62 mm) – pallet: 216 pieces;  
36 boxes with 6 pieces  
363305 | 35305 – 600 ml (Ø49 mm) – pallet: 864 pieces;  
72 boxes with 12 pieces



WAKOL MS 230 Parquet Adhesive, elastic



**Area of application:**  
Elastic 1-component MS parquet adhesive for laying mosaic, on-edge lamella parquet (min. 16 mm in width, max. 200 mm in length), strip flooring parquet (max. 80 mm in width, max. 600 mm in length), as well as multi-layered parquet on absorbent and non-absorbent subfloors indoors. WAKOL MS 230 corresponds to DIN EN ISO 17178.

**Application method:**  
trowel notch size according to TKB B3, B11, B13 or B15, WAKOL Speciality Trowel 5 or WAKOL Speciality Trowel Blade 5

**Consumption:**  
approx. 700-1300 g/m² with trowel notch, approx. 1700-1800 g/m² with WAKOL Speciality Trowel 5 or WAKOL Speciality Trowel Blade 5

**Airing time:**  
none

**Open time:**  
approx. 40 minutes

**Storage information:**  
store in a cool and dry place, not sensitive to frost

**Base:**  
MS polymer

**Order information:**  
363507 | 35307 – 18.0 kg sealed – pallet: 44 pieces



WAKOL MS 228 Ready-to-lay Parquet Adhesive, elastic



**Area of application:**  
Elastic 1-component MS parquet adhesive for laying on multi-layer parquet on absorbent and non-absorbent subfloors. WAKOL MS 228 corresponds to DIN EN ISO 17178.

**Application method:**  
trowel notch size according to TKB B3, B5, B11, B13 or B15; WAKOL Speciality Trowel 5 or WAKOL Speciality Trowel Blade 5

**Consumption:**  
approx. 800-1500 g/m² with trowel notch, approx. 1700-1800 g/m² with WAKOL Speciality Trowel 5 or WAKOL Speciality Trowel Blade 5

**Airing time:**  
none

**Open time:**  
approx. 40 minutes

**Storage information:**  
store in a cool and dry place; not sensitive to frost

**Base:**  
MS polymer

**Order information:**  
362803 | 35310 – 18.0 kg sealed – pallet: 44 pieces



WAKOL PU 385 Parquet Adhesive, shear-resistant



**Area of application:**  
Shear-resistant, 1-component PU parquet adhesive for laying of on-edge lamella parquet (min. 22 mm in width), strip and multi-layer parquet, solid wood planks, wood block RE/WE as well as cork flooring with HDF/MDF middle layer with tongue and groove resp. click-connection on absorbent and non-absorbent subfloors. WAKOL PU 385 corresponds to DIN EN ISO 17178.

**Application method:**  
trowel notch size according to TKB B3, B11, B13 or B15

**Consumption:**  
approx. 750-1450 g/m²

**Airing time:**  
none

**Open time:**  
approx. 40 minutes

**Storage information:**  
store in a cool place, not sensitive to frost

**Base:**  
polyurethane resin

**Order information:**  
367102 | 35176 – 16.0 kg sealed – pallet: 44 pieces



WAKOL PU 210 Parquet Adhesive



**Area of application:**  
Shear-resistant, 2-component PU parquet adhesive for laying of mosaic, on-edge lamella, strip, multi-layer and 10 mm solid wood lam parquet, solid wood planks, wood block RE/WE as well as for approved stratifie flooring on absorbent and non-absorbent subfloors. WAKOL PU 210 corresponds to DIN EN ISO 17178.

**Application method:**  
trowel notch size according to TKB B3, B11, B13 or B15

**Consumption:**  
approx. 700-1500 g/m²

**Airing time:**  
none

**Open time:**  
approx. 60-90 minutes

**Pot life:**  
approx. 60-70 minutes

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
polyurethane resin

**Order information:**  
368332 + 368432 | 41255 – combination pack 6.0 kg A-comp. + 0.9 kg B-comp. – pallet: 60 pieces  
368330 | 42295 – 8.0 kg A-comp. – pallet: 60 pieces  
368430 | 42296 – 1.2 kg B-comp. – pallet: 60 pieces; 5 boxes with 12 pieces



WAKOL PU 225 Parquet Adhesive



**Area of application:**  
Shear-resistant, 2-component PU parquet adhesive for laying of mosaic, on-edge lamella, strip, multi-layer and 10 mm solid wood lam parquet, solid wood planks, wood block RE/WE as well as for approved stratifie flooring on absorbent and non-absorbent subfloors. WAKOL PU 225 corresponds to DIN EN ISO 17178.

**Application method:**  
trowel notch size according to TKB B3, B11, B13 or B15

**Consumption:**  
approx. 800-1500 g/m²

**Airing time:**  
none

**Open time:**  
approx. 50 minutes

**Pot life:**  
approx. 35-40 minutes

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
polyurethane resin

**Order information:**  
368603 | 41340 – 8.9 kg A-Comp. – pallet: 44 pieces  
368703 | 41341 – 1.1 kg B-Comp. – pallet: 440 pieces; 40 boxes with 11 pieces  
368604 + 368704 | 41256 – combination pack 6.0 kg A-comp. + 0.75 kg B-comp. – pallet: 60 pieces



## WAKOL PU 220 Parquet Adhesive



### Area of application:

Shear-resistant, 2-component PU parquet adhesive for laying of 10 mm solid wood lam parquet flooring, mosaic parquet, on-edge lamella parquet, strip parquet, multi-layer parquet, solid wood planks, wood-block RE/WE on absorbent and non-absorbent subfloors indoors. WAKOL PU 220 corresponds to DIN EN ISO 17178.

### Application method:

trowel notch size according to TKB B3, B11, B13 or B15

### Consumption:

approx. 750-1500 g/m<sup>2</sup>

### Airing time:

none

### Open time:

approx. 130 minutes

### Pot life:

approx. 100 minutes

### Storage information:

not below +5°C, sensitive to frost

### Base:

polyurethane resin

### Order information:

368105 | 35193 – 12.0 kg A-comp. – pallet: 44 pieces  
368905 | 35192 – 1.12 kg B-comp. – pallet: 440 pieces; 40 boxes with 11 pieces



## WAKOL PU 216 Parquet Adhesive



### Area of application:

Shear-resistant, 2-component PU parquet adhesive for laying of mosaic, on-edge lamella, strip, multi-layer and 10 mm solid wood lam parquet, solid wood planks as well as wood block RE/WE on absorbent and non-absorbent subfloors indoors. WAKOL PU 216 corresponds to DIN EN ISO 17178.

### Application method:

trowel notch size according to TKB B3, B11, B13 or B15

### Consumption:

approx. 750-1500 g/m<sup>2</sup>

### Airing time:

none

### Open time:

approx. 70 minutes

### Pot life:

approx. 35-40 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

polyurethane resin

### Order information:

369005 | 35196 – 7.0 kg A-comp. – pallet: 60 pieces  
368405 | 35195 – 0.75 kg B-comp. – pallet: 60 pieces; 5 boxes with 12 pieces  
369003 | 35197 – 11.0 kg A-Comp. – pallet: 44 pieces  
368413 | 35194 – 1.19 kg B-Comp. – pallet: 440 pieces; 40 boxes with 11 pieces



## WAKOL PU 215 Parquet Adhesive



### Area of application:

Shear-resistant, 2-component PU parquet adhesive for laying of 10 mm solid wood lam parquet flooring, mosaic parquet, on-edge lamella parquet, strip parquet, multi-layer parquet, solid wood planks, wood-block RE/WE on absorbent and non-absorbent subfloors indoors. WAKOL PU 215 corresponds to DIN EN ISO 17178.

### Application method:

trowel notch size according to TKB B3, B11, B13 or B15

### Consumption:

approx. 750-1550 g/m<sup>2</sup>

### Airing time:

none

### Open time:

approx. 90 minutes

### Pot life:

approx. 80 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

polyurethane resin

### Order information:

368403 | 35198 – 1.12 kg B-comp. – pallet: 440 pieces; 40 boxes with 11 pieces  
368803 | 35201 – 12.0 kg A-comp. – pallet: 44 pieces  
368404 | 35195 – 0.75 kg B-comp. – pallet: 60 pieces; 5 boxes with 12 pieces  
368804 | 35200 – 8.0 kg A-comp. – pallet: 60 pieces



## WAKOL D 3513 Cork Pre-Coating



### Area of application:

Latex adhesive for machine-operated pre-coating of natural cork flooring that is to be laid by contact procedure. WAKOL D 3513 may be used only in combination with WAKOL D 3540 Cork Contact Adhesive. Pre-coating is possible up to 6 months prior to laying.

### Application method:

roller application with suitable machine on the back of the floor covering

### Consumption:

approx. 80-100 g/m<sup>2</sup>

### Airing time:

approx. 60 minutes

### Open time:

approx. 60-90 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

natural latex

### Order information:

351309 | 39133 – 10.0 kg – pallet: 60 pieces



## WAKOL D 3540 Cork Contact Adhesive



### Area of application:

Latex adhesive for laying cork tiles according to DIN EN 12104 with non-treated or treated surface on absorbent and non-absorbent subfloors. Also suitable for cork wall coverings, textile flooring, linoleum, caoutchouc flooring and deflectors. WAKOL D 3540 corresponds to DIN EN ISO 22636.

### Application method:

WAKOL Primer Roller or velour roller on cork wall coverings, for carpet flooring with brush or trowel notch size according to TKB A1, A2 or A3

### Consumption:

minimum 250 g/m<sup>2</sup> for laying cork, otherwise 150-650 g/m<sup>2</sup>

### Airing time:

approx. 30-45 minutes on absorbent subfloors, approx. 60-90 minutes on non-absorbent subfloors and on the back of the floor covering

### Open time:

approx. 120-180 minutes, with pre-coating approx. 60-90 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

latex/acrylate dispersion

### Order information:

354004 | 46742 – 11.0 kg – pallet: 44 pieces  
354008 | 30100 – 5.0 kg – pallet: 80 pieces  
354009 | 38506 – 2.5 kg – pallet: 120 pieces  
354010 | 35827 – 0.8 kg – pallet: 384 pieces; 32 boxes with 12 pieces



## WAKOL D 1640 Parquet Adhesive



### Area of application:

Shear-resistant dispersion parquet adhesive for laying of mosaic, on-edge lamella parquet (min. 16 mm in width, max. 200 mm in length) and strip parquet in oak as well as multi-layer parquet up to 220 cm length on new, good absorbent cement screeds which are in accordance with the standard. WAKOL D 1640 corresponds to DIN EN ISO 17178.

### Application method:

trowel notch size according to TKB B3, B11 or B13

### Consumption:

approx. 700-1300 g/m<sup>2</sup>

### Airing time:

none

### Open time:

approx. 10-15 minutes

### Storage information:

not below +5 °C, sensitive to frost

### Base:

synthetic resin dispersion

### Order information:

321704 | 24476 – 14.0 kg – pallet: 44 pieces





WAKOL D 1690 Parquet Adhesive



**Area of application:**  
Shear-resistant dispersion parquet adhesive for laying of mosaic, on-edge lamella parquet (min. 16 mm in width, max. 200 mm in length) and strip parquet in oak as well as multi-layer parquet on absorbent subfloors. WAKOL D 1690 corresponds to DIN EN ISO 17178.

**Application method:**  
trowel notch size according to TKB B3 or B11

**Consumption:**  
approx. 700-1100 g/m²

**Airing time:**  
none

**Open time:**  
approx. 15 minutes

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
synthetic resin dispersion

**Order information:**  
322203 | 35903 – 14,0 kg – pallet: 44 pieces

WAKOL D 6085 Wood Glue



**Area of application:**  
Wood glue for all heavy-duty requirements such as mortise, dowel and joint gluing. WAKOL D 6085 is especially suited for the tongue and groove engineered flooring gluing of ready-to-lay parquet, flooring stratifie and chipboard. WAKOL D 6085 corresponds to load class D 3.

**Application method:**  
for surface bonding with notched trowel for matchboard gluing with sprayer nozzle of the glue bottle

**Consumption:**  
approx. 150-200 g/m², with Wood Glue bottle approx. 15-20 g/running meter for matchboard gluing

**Airing time:**  
none

**Open time:**  
approx. 6 minutes

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
synthetic resin dispersion

**Order information:**  
316307 | 35656 – 0.75 kg – pallet: 480 pieces; 80 boxes with 6 pieces

WAKOL MS 335 Repair Resin



**Area of application:**  
Fast-curing, silane modified repair resin for restoring hollow spots in parquet floors. WAKOL MS 335 Repair Resin can be applied independently from the used parquet adhesive.

**Hardening time:**  
approx. 2 hours

**Storage information:**  
store in a cool and dry place; not sensitive to frost

**Base:**  
MS polymer

**Order information:**  
361503 | 35282 – 0.6 kg – pallet: 308 pieces; 77 boxes with 4 pieces

WAKOL PU 4519 2K-PU Accelerator



**Area of application:**  
Accelerator for increasing the reaction speed of two-component polyurethane adhesives.

**Dosage:**  
1-5 caps of 15 ml depending on the product and the required acceleration

**Storage information:**  
store in a cool and dry place, not sensitive to frost

**Base:**  
polyurethane catalyst

**Order information:**  
451906 | 35157 – 0.9 kg – pallet: 320 pieces

WAKOL PK 4535 Colour Paste, brown



**Area of application:**  
Brown colour paste to stain all kind of Wakol MS-parquet adhesives, Wakol polyurethane adhesives and Wakol dispersion adhesives.

**Dosage:**  
1-2 tubes per packaging Wakol parquet adhesive

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
pigment concentrate

**Order information:**  
453505 | 30117 – 0.15 kg (brown) – pallet: 1.950 pieces; 195 boxes with 10 pieces

## WAKOL D 3110 Modular Flooring Fixation



**Area of application:**  
Dispersion-based fixation for laying modular textile flooring, self-laying LVT flooring and CV flooring without the function of multiple replacements on absorbent and non-absorbent subfloors. For conductive laying, mix WAKOL D 3110 with WAKOL DL 352 Conductive Dispersion in a ratio of 4,4 :1.

**Application method:**  
WAKOL Primer Roller or velour roller

**Consumption:**  
approx. 80-120 g/m<sup>2</sup> with roller

**Airing time:**  
approx. 20 minutes on absorbent subfloors, approx. 35 minutes on non-absorbent subfloors

**Open time:**  
approx. 24 hours

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
acrylate dispersion

**Order information:**  
311003 | 35887 – 11.0 kg – pallet: 40 pieces

## WAKOL D 965 Tackifier Dispersion



**Area of application:**  
Tackifier dispersion for anti-slip laying of self-laying carpet tiles with bitumen/fleece, PVC or PUR backing on absorbent and non-absorbent subfloors.

**Application method:**  
WAKOL Primer Roller or velour roller

**Consumption:**  
approx. 80-120 g/m<sup>2</sup>

**Airing time:**  
approx. 15-45 minutes

**Open time:**  
approx. 24 hours

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
synthetic resin dispersion

**Order information:**  
310203 | 37061 – 10.0 kg – pallet: 40 pieces

## WAKOL D 3202 Universal Fixation



**Area of application:**  
Dispersion-based fixation for laying CV flooring as well as textile flooring with latex foam backing or synthetic double backing on existing floor coverings, levelled concrete subfloors and P4 to P7 chipboard. Fixed covering can be removed again without damage to the subfloors.

**Application method:**  
trowel notch size according to TKB A2, WAKOL Primer Roller or velour roller

**Consumption:**  
approx. 200-300 g/m<sup>2</sup>

**Airing time:**  
approx. 10-20 minutes on absorbent subfloors, approx. 45-60 minutes on non-absorbent subfloors

**Open time:**  
approx. 20-30 minutes

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
polymer dispersion

**Blue Angel:**  
DE-UZ 113

**Order information:**  
320203 | 35876 – 12.0 kg – pallet: 40 pieces  
320205 | 35875 – 3.0 kg – pallet: 120 pieces

## WAKOL DL 3078 Conductive Primer



**Area of application:**  
Ready-to-use conductive dispersion-based primer for subsequent conductive laying of textile and elastic flooring. WAKOL DL 3078 replaces the laying of a copper band net.

**Application method:**  
WAKOL Primer Roller

**Consumption:**  
approx. 120-150 g/m<sup>2</sup>

**Drying time:**  
approx. 3-5 hours

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
acrylate dispersion

**Order information:**  
307803 | 25687 – 10.0 kg – pallet: 60 pieces

## WAKOL D 3201 VliesFix



**Area of application:**  
Dispersion-based fixation for laying dimensionally stable textile flooring with fleece backing and approved by the manufacturer for fixation, on smooth, existing floor coverings, levelled subfloors and P4 to P7 chipboard in living areas. Fixed covering can be easily removed without damage to the subfloors.

**Application method:**  
WAKOL Primer Roller or velour roller

**Consumption:**  
approx. 120 g/m<sup>2</sup>

**Airing time:**  
approx. 10-15 minutes on absorbent subfloors, approx. 20-30 minutes on dense subfloors

**Open time:**  
approx. 30 minutes

**Storage information:**  
not below +5 °C; sensitive to frost

**Base:**  
acrylate dispersion

**Order information:**  
320103 | 35879 – 12.0 kg – pallet: 40 pieces  
320105 | 35878 – 3.0 kg – pallet: 120 pieces

## WAKOL DL 3365 StarLeit



**Area of application:**  
Light-coloured, fibre-containing dispersion adhesive for the laying of conductive PVC, textile and linoleum flooring as well as for conductive caoutchouc flooring of thickness up to 4 mm on appropriately prepared subfloors. WAKOL DL 3365 corresponds to DIN EN ISO 22636.

**Application method:**  
trowel notch size according to TKB S2, Pajarito 7 or Pajarito 25; trowel notch enclosed

**Consumption:**  
approx. 250-550 g/m<sup>2</sup>

**Airing time:**  
approx. 10-15 minutes

**Open time:**  
approx. 20-40 minutes

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
acrylate dispersion

**Order information:**  
336504 | 30098 – 12.0 kg – pallet: 40 pieces



## WAKOL D 3110 Modular Flooring Fixation



**Area of application:**  
Dispersion-based fixation for laying modular textile flooring, self-laying LVT flooring and CV flooring without the function of multiple replacements on absorbent and non-absorbent subfloors. For conductive laying, mix WAKOL D 3110 with WAKOL DL 352 Conductive Dispersion in a ratio of 4,4 :1.

**Application method:**  
WAKOL Primer Roller or velour roller

**Consumption:**  
approx. 80-120 g/m<sup>2</sup> with roller

**Airing time:**  
approx. 20 minutes on absorbent subfloors, approx. 35 minutes on non-absorbent subfloors

**Open time:**  
approx. 24 hours

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
acrylate dispersion

**Order information:**  
311003 | 35887 – 11.0 kg – pallet: 40 pieces

## WAKOL DL 352 Conductive Dispersion



**Area of application:**  
Conductive dispersion in combination with WAKOL D 3110 Modular Flooring Fixation for producing a conductive slip brake or an adhesive fixation for appropriately equipped modular textile flooring.

**Mixture:**  
4.4 parts WAKOL D 3110 + 1 part WAKOL DL 352

**Usage:**  
only in combination with WAKOL D 3110

**Storage information:**  
not below +5 °C, sensitive to frost

**Base:**  
special carbon black

**Order information:**  
450102 | 35644 – 5.0 kg – palette: 60 pieces

## WAKOL KB 199 Copper Tape



**Area of application:**  
Self-adhesive copper tape for electrical bonding for conductive flooring

**Storage information:**  
not sensitive to frost

**Base:**  
Copper

**Order information:**  
595741 | 46477 – Roll 50 m, 10 mm wide – 1 box with 1 piece each

## WAKOL AS 130 Seaming Tape



**Area of application:**  
Polyester fleece tape for bonding artificial grass sheets with each other in joint sections indoors and outdoors.

**Laying:**  
in the system with WAKOL PU 272

**Consumption:**  
corresponding to the joint length

**Storage information:**  
not sensitive to frost

**Base:**  
polyester fleece

**Order information:**  
595612 | 41374 – Roll 100 m, 300 mm wide – pallet: 80 pieces; 16 boxes with 5 pieces

## WAKOL AS 151 Sealing Sheet



**Area of application:**  
System component for waterproofing wet areas in private and commercial areas under parquet and resilient flooring.

**Laying:**  
glued over the entire surface, with sheets closely abutting one another

**Consumption:**  
corresponding to the room size

**Storage information:**  
store roll upright, not sensitive to frost

**Base:**  
polypropylene fleece

**Order information:**  
595602 | 35031 – Roll 20 m, 1 m wide, 0,5 mm thick – pallet: 24 pieces; 24 boxes with 1 piece

## WAKOL AS 152 Sealing Tape



**Area of application:**  
System component for waterproofing wet areas in private and commercial areas under parquet and resilient flooring.

**Laying:**  
glued over the entire surface, in the system with WAKOL AS 151

**Consumption:**  
corresponding to the room size

**Storage information:**  
not sensitive to frost

**Base:**  
polypropylene fleece

**Order information:**  
595603 | 35030 – Roll 50 m, 120 mm wide – pallet: 120 pieces; 120 boxes with 1 piece

## WAKOL AS 153 Sealing Corners, inner



**Area of application:**  
System component for waterproofing wet areas in private and commercial areas under parquet and resilient flooring.

**Laying:**  
glued over the entire surface, in the system with WAKOL AS 151

**Consumption:**  
1 pc. per inner corner

**Storage information:**  
not sensitive to frost

**Base:**  
polypropylene fleece

**Order information:**  
595604 | 35029 – 5 pieces - each 119 x 119 x 60 mm –  
pallet: 2.000 pieces; 400 boxes with 5 pieces



## WAKOL AS 156 Sealing Collar, large



**Area of application:**  
Polyethylene foil on both sides laminated with polypropylene fleece for feedthrough of water pipes with 65-200 mm diameter.  
System component for waterproofing wet areas in private and commercial areas under parquet and resilient flooring.

**Laying:**  
glued over the entire surface, in the system with WAKOL AS 151

**Consumption:**  
1 pc. per feedthrough

**Storage information:**  
not sensitive to frost

**Base:**  
polypropylene fleece

**Order information:**  
595607 | 41667 – 5 pieces - each 425 x 425 mm –  
pallet: 1.000 pieces; 200 boxes with 5 pieces



## WAKOL AS 154 Sealing Corners, outer



**Area of application:**  
System component for waterproofing wet areas in private and commercial areas under parquet and resilient flooring.

**Laying:**  
glued over the entire surface, in the system with WAKOL AS 151

**Consumption:**  
1 pc. per outer corner


**Storage information:**  
not sensitive to frost

**Base:**  
polypropylene fleece

**Order information:**  
595605 | 35028 – 5 pieces - each 115 x 115 x 60 mm –  
pallet: 2.000 pieces; 400 boxes with 5 pieces



## WAKOL AS 157 Stretch Collar



**Area of application:**  
Polyethylene foil on both sides laminated with polypropylene fleece for feedthrough of water pipes with 40-65 mm diameter.  
System component for waterproofing wet areas in private and commercial areas under parquet and resilient flooring.

**Laying:**  
glued over the entire surface, in the system with WAKOL AS 151

**Consumption:**  
1 pc. per feedthrough


**Storage information:**  
not sensitive to frost

**Base:**  
polypropylene fleece

**Order information:**  
595608 | 41668 – 5 pieces - each 150 x 150 mm –  
pallet: 500 pieces; 100 boxes with 5 pieces



## WAKOL AS 155 Sealing Collar, small



**Area of application:**  
Polyethylene foil on both sides laminated with polypropylene fleece for feedthrough of water pipes with 15-30 mm diameter.  
System component for waterproofing wet areas in private and commercial areas under parquet and resilient flooring.

**Laying:**  
glued over the entire surface, in the system with WAKOL AS 151

**Consumption:**  
1 pc. per feedthrough

**Storage information:**  
not sensitive to frost

**Base:**  
polypropylene fleece

**Order information:**  
595606 | 41666 – 5 pieces - each 140 x 140 mm –  
pallet: 500 pieces; 100 boxes with 5 pieces



## WAKOL AR 115 Reinforcement Fibre Sheet



**Area of application:**  
Alkali-resistant fibreglass mat for reinforcing approved, self-flowing Wakol levelling compounds for use on cracked and slightly vibrating subfloors without counter movements, crack width up to max. 3 mm, old mineral subfloors, wooden subfloors, screed damages and mixed subfloors indoors.

**Laying:**  
overlapping sheets

**Consumption:**  
corresponding to the room size

**Storage information:**  
store in a cool and dry place, not sensitive to frost

**Base:**  
fibre glass fabric

**Order information:**  
595506 | 36013 – Roll 100 m, 0.90 m wide –  
pallet: 24 pieces



WAKOL AR 116 Refurbishment Fibre Sheet



**Area of application:**  
Alkali-resistant fibreglass strips laminated on backing fleece for the usage on cracks and joints in subfloors without counter movements up to maximum 5 mm width instead of force-fit connection, screed damages and mixed subfloors indoors.

**Laying:**  
partially over affected areas

**Consumption:**  
corresponding to the areas to be renovated

**Storage information:**  
store in a cool and dry place, not sensitive to frost

**Base:**  
fibre glass fabric

**Order information:**  
595507 | 36014 – Roll 45 m, 0.80 m wide – pallet: 24 pieces

WAKOL RP 104 Decoupling Sheet, 4 mm



**Area of application:**  
Polyester fibre sheet for decoupling and soundproofing reduction under bonded parquet indoors also appropriate for applying a levelling layer before bonding textile and elastic flooring.

**Laying:**  
completely cover, with sheets closely abutting one another

**Consumption:**  
corresponding to the room size

**Footfall sound reduction (as per DIN EN ISO 10140-3):**  
depends on top covering, e.g. approx. 13 dB with 10 mm parquet

**Storage information:**  
store boxes flat, not sensitive to frost

**Base:**  
polyester fibre mixture

**Order information:**  
590402 | 34984 – 15 sheets - each 100 x 60 cm, 4 mm thick – pallet: 150 pieces; 10 boxes with 15 pieces



WAKOL AR 150 Reinforcement Fabric



**Area of application:**  
Alkali-resistant fibreglass fabric for reinforcing levelling compounds on inhomogeneous subfloors, wood planks and wood product tile subfloors as well as in sports facility construction in systems with WAKOL D 3060 Plastification Additive and Wakol levelling compound.

**Laying:**  
overlapping sheets, fixed on the subfloor

**Consumption:**  
corresponding to the room size

**Storage information:**  
store roll upright, not sensitive to frost

**Base:**  
fibre glass fabric

**Order information:**  
595502 | 35032 – Roll 50 m, 1 m wide – pallet: 30 pieces



WAKOL RP 107 Decoupling Sheet, 7 mm



**Area of application:**  
Polyester fibre sheet for decoupling and soundproofing reduction under bonded parquet indoors also appropriate for applying a levelling layer before bonding textile and elastic flooring.

**Laying:**  
completely cover, with sheets closely abutting one another

**Consumption:**  
one after the other corresponding to the room size

**Footfall sound reduction (as per DIN EN ISO 10140-3):**  
depending on the top covering, e.g. approx. 14 dB with 10 mm of parquet

**Storage information:**  
store boxes flat, not sensitive to frost

**Base:**  
polyester fibre mixture

**Order information:**  
590907 | 34983 – 9 sheets - each 100 x 60 cm, 7 mm thick – pallet: 90 pieces; 10 boxes with 9 pieces



WAKOL EM 140 Uncoupling Fleece



**Area of application:**  
Light green polyester fleece for decoupling and low tension reinforcement under bonded parquet indoors also appropriate for applying a levelling layer before bonding textile and elastic flooring.

**Laying:**  
completely cover, with sheets closely abutting one another

**Consumption:**  
corresponding to the room size

**Storage information:**  
store roll upright, not sensitive to frost

**Base:**  
polyester fleece

**Order information:**  
590303 | 41705 – Roll 50 m, 1 m wide, 1,1 mm tick – pallet: 12 pieces

WAKOL RP 109 Decoupling Sheet, 9 mm



**Area of application:**  
Polyester fibre sheet for decoupling and soundproofing reduction under bonded parquet indoors also appropriate for applying a levelling layer before bonding textile and elastic flooring.

**Laying:**  
completely cover, with sheets closely abutting one another

**Consumption:**  
corresponding to the room size

**Footfall sound reduction (as per DIN EN ISO 10140-3):**  
depends on top covering, e.g. approx. 14 dB with 10 mm parquet

**Storage information:**  
store boxes flat, not sensitive to frost

**Base:**  
polyester fibre mixture

**Order information:**  
590502 | 34982 – 10 sheets - each 100 x 60 cm, 9 mm thick – pallet: 100 pieces; 10 boxes with 10 pieces



WAKOL RP 115 Decoupling Sheet, 15 mm



**Area of application:**  
Polyester fibre sheet for decoupling and soundproofing reduction under bonded parquet indoors also appropriate for applying a levelling layer before bonding textile and elastic flooring.

**Laying:**  
completely cover, with sheets closely abutting one another

**Consumption:**  
corresponding to the room size

**Footfall sound reduction (as per DIN EN ISO 10140-3):**  
depends on top covering, e.g. approx. 14 dB with 10 mm parquet

**Storage information:**  
store boxes flat, not sensitive to frost

**Base:**  
polyester fibre mixture

**Order information:**  
590802 | 34981 – 6 sheets - each 100 x 60 cm, 15 mm thick – pallet: 60 pieces; 10 boxes with 6 pieces



WAKOL RP 709 Project Decoupling Sheet, 9 mm



**Area of application:**  
Polyester fibre sheet for decoupling and soundproofing reduction under bonded parquet indoors. Also appropriate for applying a levelling layer before bonding textile and elastic flooring.

**Laying:**  
completely cover, with sheets closely abutting one another

**Consumption:**  
corresponding to the room size

**Footfall sound reduction (as per DIN EN ISO 10140-3):**  
depends on top covering, e.g. approx. 14 dB with 10 mm parquet

**Storage information:**  
store boxes flat, not sensitive to frost

**Base:**  
polyester fibre mixture

**Order information:**  
590579 | 36006 – 10 sheets - each 100 x 60 cm, 9 mm thick – pallet: 100 pieces; 10 boxes with 10 pieces



WAKOL RP 704 Project Decoupling Sheet, 4 mm



**Area of application:**  
Polyester fibre sheet for decoupling and soundproofing reduction under bonded parquet indoors also appropriate for applying a levelling layer before bonding textile and elastic flooring.

**Laying:**  
completely cover, with sheets closely abutting one another

**Consumption:**  
corresponding to the room size

**Footfall sound reduction (as per DIN EN ISO 10140-3):**  
depends on top covering, e.g. approx. 13 dB with 10 mm parquet

**Storage information:**  
store boxes flat, not sensitive to frost

**Base:**  
polyester fibre mixture

**Order information:**  
590474 | 34980 – 15 sheets - each 100 x 60 cm, 4 mm thick – pallet: 150 pieces; 10 boxes with 15 pieces



WAKOL RP 715 Project Decoupling Sheet, 15 mm



**Area of application:**  
Polyester fibre sheet for decoupling and soundproofing reduction under bonded parquet indoors. Also appropriate for applying a levelling layer before bonding textile and elastic flooring.

**Laying:**  
completely cover, with sheets closely abutting one another

**Consumption:**  
corresponding to the room size

**Footfall sound reduction (as per DIN EN ISO 10140-3):**  
depends on top covering, e.g. approx. 13 dB with 10 mm parquet

**Storage information:**  
store boxes flat, not sensitive to frost

**Base:**  
polyester fibre mixture

**Order information:**  
590872 | 41372 – 5 sheets - each 100 x 60 cm, 15 mm thick – pallet: 50 pieces; 10 boxes with 5 pieces



WAKOL RP 707 Project Decoupling Sheet, 7 mm



**Area of application:**  
Polyester fibre sheet for decoupling and soundproofing reduction under bonded parquet indoors. Also appropriate for applying a levelling layer before bonding textile and elastic flooring.

**Laying:**  
completely cover, with sheets closely abutting one another

**Consumption:**  
corresponding to the room size

**Footfall sound reduction (as per DIN EN ISO 10140-3):**  
depends on top covering, e.g. approx. 14 dB with 10 mm parquet

**Storage information:**  
store boxes flat, not sensitive to frost

**Base:**  
polyester fibre mixture

**Order information:**  
590977 | 45802 – 10 sheets - each 100 x 60 cm, 7 mm thick – pallet: 100 pieces; 10 boxes with 10 pieces



WAKOL TS 102 Footfall Soundproofing Mat, 2 mm



**Area of application:**  
Cork/polyurethane foam matting for improving the footfall soundproofing and heat insulation of flooring structures in old and new buildings. WAKOL TS 102 is suitable as soundproofing material under PVC, CV, textile, linoleum and caoutchouc flooring, as well as mosaic parquet (cubes), on edge lamella, strip, multi-layer parquet, wood block RE/WE, solid wood planks (type of wood oak, max. 16 cm in width) and stratified flooring indoors.

**Laying:**  
completely cover, with mats closely abutting one another

**Consumption:**  
corresponding to the room size

**Footfall sound reduction (as per DIN EN ISO 10140-3):**  
19 dB in combination with 10 mm multi-layer parquet, 19 dB in combination with 3 mm PVC, 17 dB in combination with 3 mm rubber

**Storage information:**  
store roll upright, not sensitive to frost

**Base:**  
cork/PU-foam

**Order information:**  
590704 | 39194 – Roll 30 m, 1 m wide, 2 mm thick – pallet: 11 pieces





WAKOL TS 103 Footfall Soundproofing Mat, 3 mm



**Area of application:**  
Cork/polyurethane foam matting for improving the footfall soundproofing and heat insulation of flooring structures in old and new buildings. WAKOL TS 103 is suitable as soundproofing material under PVC, CV, textile, linoleum and caoutchouc flooring, as well as strip, multi-layer parquet, wood block RE/WE, solid wood planks (type of wood oak, max. 16 cm in width) and stratifie flooring indoors.

**Laying:**  
completely cover, with mats closely abutting one another

**Consumption:**  
corresponding to the room size

**Footfall sound reduction (as per DIN EN ISO 10140-3):**  
18 dB in combination with 10 mm multi-layer parquet, 20 dB in combination with 3 mm PVC, 17 dB in combination with 3 mm rubber

**Storage information:**  
store roll upright, not sensitive to frost

**Base:**  
cork/PU-foam

**Order information:**  
590705 | 34962 – Roll 35 m, 1 m wide, 3 mm thick – pallet: 6 pieces



WAKOL TS 112 Footfall Soundproofing Mat, 2 mm



**Area of application:**  
Cork/polyurethane foam matting for improving the footfall soundproofing and heat insulation of flooring structures in old and new buildings. WAKOL TS 112 is, according to DIN EN 13501-1 classified with B<sub>fl,S1</sub> (hardly flammable), and suitable as soundproofing material under PVC, CV, textile, linoleum and caoutchouc flooring, as well as mosaic parquet (cubes), on edge lamella, strip, multi-layer parquet, wood block RE/WE, solid wood planks (type of wood oak, max. 16 cm in width) and stratifie flooring indoors.

**Laying:**  
completely cover, with mats closely abutting one another

**Consumption:**  
corresponding to the room size

**Reaction to fire (according to ISO 11 925/EN 13 501):**  
Bfl-S1

**Footfall sound reduction (as per DIN EN ISO 10140-3):**  
19 dB in combination with 10 mm multi-layer parquet

**Storage information:**  
store roll upright, not sensitive to frost

**Base:**  
cork/PU-foam

**Order information:**  
590706 | 34961 – Roll 30 m, 1 m wide, 2 mm thick – pallet: 11 pieces



WAKOL TS 160 Footfall Soundproofing Mat



**Area of application:**  
Polypropylene soundproofing mat with single-sided aluminium lamination for improving the footfall sound insulation. WAKOL TS 160 Footfall Soundproofing Mat has cut-outs for accommodating WAKOL MS 232 Parquet Adhesive, elastic or WAKOL MS 262 Parquet Adhesive, firm-elastic, and is suitable for laying strip parquet and solid wood planks up to max. 18 cm in width and multi-layer parquet as of 90 cm in length indoors.

**Laying:**  
loosely, with the metallic side up

**Consumption:**  
corresponding to the room size

**Footfall sound reduction (as per DIN EN ISO 10140-3):**  
17 dB in combination with 10 mm ready-to-lay parquet

**Storage information:**  
store roll upright, not sensitive to frost

**Base:**  
polypropylene

**Order information:**  
590602 | 25523 – Roll 12 m, 1.25 m wide, 3 mm thick – pallet: 12 pieces



WAKOL TS 170 Footfall Soundproofing Sheet



**Area of application:**  
Natural cork mat for improving footfall sound insulation with cut-outs for accommodating WAKOL MS 232 Parquet Adhesive, elastic or WAKOL MS 262 Parquet Adhesive, firm-elastic, and suitable for laying strip parquet and solid wood planks up to max. 18 cm in width and multi-layer parquet as of 90 cm in length as well as for cork on HDF/MDF carrier with tongue and groove joining or click joining on absorbent and non-absorbent subfloors indoors.

**Laying:**  
loosely, in irregular pattern

**Consumption:**  
corresponding to the room size

**Footfall sound reduction (as per DIN EN ISO 10140-3):**  
15 dB in combination with 14 mm multi-layer parquet

**Storage information:**  
store boxes flat, not sensitive to frost

**Base:**  
natural cork

**Order information:**  
590604 | 34960 – 52 sheets - each 915 x 610mm, 2.5 mm thick – pallet: 1.040 pieces; 20 boxes with 52 pieces



WAKOL UM 110 Blocking Mat



**Area of application:**  
Loosely laid mat with napped backing for blocking excessive residual moisture in cement paving up to max. 5 CM% / 95 corresponding RH %, calcium sulphate concrete up to max. 2 CM% / 85 corresponding RH %, raw concrete ceiling up to max. 7% by weight / 95 corresponding RH %, as well as for uncoupling subfloors not ready for laying and for protecting existing floors for subsequently laying of textile flooring, PVC flooring, CV flooring and LVT flooring in planks indoors.

**Laying:**  
loosely, with sheets closely abutting one another

**Consumption:**  
corresponding to the room size

**Storage information:**  
store roll upright, not sensitive to frost

**Base:**  
fibreglass, bonded

**Order information:**  
591802 | 34959 – 35 m roll, 2 m wide, 1.5 mm thick – pallet: 12 pieces



WAKOL MS 425 Decking Sealant, black



**Area of application:**  
One-component, black-coloured, elastic sealant for grouting full-bonded decking made of wood, such as teak, pitch pine, oak, sipo, as well as synthetic materials (except polyethylene or polypropylene) indoors and outdoors.

**Application method:**  
commercially available tubular bag press or WAKOL Applicator 50

**Open time:**  
approx. 15-20 minutes

**Hardening time:**  
approx. 24 h for 2.5 mm, approx. 48 h for 3.5 mm thickness

**Storage information:**  
not sensitive to frost

**Base:**  
MS polymer

**Order information:**  
366906 | 43984 – 600 ml – pallet: 720 pieces; 60 boxes with 12 pieces



WAKOL L 1806 Adhesion Promoter



**Area of application:**  
Solvent-based primer to increase the adhesion of WAKOL MS 425 Decking Sealant, black for grouting wooden ship decks indoors and outdoors.

**Application method:**  
brush

**Drying time:**  
min. 15 minutes, max. 4 h

**Storage information:**  
not sensitive to frost

**Base:**  
organic solvent mixture

**Order information:**  
180606 | 43983 – 250 ml – 1 box with 9 pieces

WAKOL KB 189 Skirting Adhesive Tape, 90 mm



**Area of application:**  
Double-sided, strong adhesive tape with string core for bonding of floor coverings as wall skirting, prefabricated rubber or linoleum cove bases, covering strips made of rubber, linoleum or textile coverings and soft skirting (up to 100 mm) indoors.

**Storage information:**  
not sensitive to frost

**Base:**  
polyacrylate with yarn core

**Order information:**  
595721 | 45801 – Roll 50 m, 90 mm wide, 0.38 mm thick – pallet: 180 pieces; 60 boxes with 3 pieces

WAKOL RT 5960 Cleaning Cloth



**Area of application:**  
Impregnated towels for cleaning hands, especially if soiled with non-hardened PU adhesives, oils, grease and paint. Also suitable for cleaning tools. Bucket with reclosable removal opening.

**Storage information:**  
store in a cool and dry place, not sensitive to frost

**Base:**  
polyethylene

**Order information:**  
596003 | 36030 – 150 units in bucket – pallet: 120 pieces; 30 boxes with 4 pieces

WAKOL KB 185 Skirting Adhesive Tape, 50 mm



**Area of application:**  
Tape, on both sides with strong adhesive covered, with yarn core for bonding looped carpet skirting board with different backing formats, soft skirting (up to 60 mm) and rubber skirting (up to 60 mm) indoors.

**Storage information:**  
not sensitive to frost

**Base:**  
polyacrylate with yarn core

**Order information:**  
595712 | 44348 – Roll 50 m, 50 mm wide, 0.23 mm thick – pallet: 300 pieces; 60 boxes with 5 pieces

WAKOL RV 105 Neoprene Dilution



**Area of application:**  
For cleaning tools.

**Storage information:**  
store in a cool and dry place, not sensitive to frost

**Base:**  
organic solvent

**Order information:**  
180306 | 35142 – 4.0 kg – pallet: 126 pieces

WAKOL KB 183 Skirting Adhesive Tape, 35 mm



**Area of application:**  
Tape, on both sides with strong adhesive covered, with yarn core for bonding solid core skirting, carpet skirting, textile and needle-punch flooring skirting and soft skirting (up to 50 mm) indoors.

**Storage information:**  
not sensitive to frost

**Base:**  
polyacrylate with yarn core

**Order information:**  
595711 | 41703 – Roll 50 m, 35 mm wide, 0.38 mm thick – pallet: 480 pieces; 60 boxes with 8 pieces



### WAKOL KB 182 Staircase Adhesive Tape, 240 mm



**Area of application:**  
Double-sided adhesive tape with string core for bonding of rubber form steps, flooring with separately attached stair nosing edge profiles such as rubber coverings, homogeneous PVC/CV flooring and linoleum up to 2.5 mm indoors.

**Storage information:**  
not sensitive to frost

**Base:**  
polyacrylate with yarn core

**Order information:**  
595731 | 45800 – Roll 50 m, 240 mm wide, 0,23 mm thick



### WAKOL KB 181 Skirting Adhesive Tape, 25 mm



**Area of application:**  
Tape, on both sides with strong adhesive covered, with yarn core for bonding solid core skirting, carpet skirting, textile and needle-punch flooring skirting and soft skirting (up to 40 mm) indoors.

**Storage information:**  
not sensitive to frost

**Base:**  
polyacrylate with yarn core

**Order information:**  
595709 | 47494 – Roll 50 m, 25 mm wide, 0.38 mm thick – pallet: 660 pieces; 60 boxes with 11 pieces



### WAKOL KB 180 Skirting Adhesive Tape, 100 mm



**Area of application:**  
Tape, on both sides with strong adhesive covered, with yarn core for bonding looped carpet skirting board with different backing formats, soft skirting (up to 100 mm) and rubber skirting (up to 100 mm) indoors.

**Storage information:**  
not sensitive to frost

**Base:**  
polyacrylate with yarn core

**Order information:**  
595720 | 47495 – Roll 50 m, 100 mm wide, 0.38 mm thick – pallet: 180 pieces; 60 boxes with 3 pieces



### WAKOL RS 5950 Screed Edging Strips, 100 mm



**Area of application:**  
Permanently elastic screed edging strips made of polyethylene with adhesive strips for screed work, WAKOL Z 560 Rapid Screed, WAKOL Z 590 Light Screed and screeds made of WAKOL EP 219 Screed Binder with WAKOL S 25 Elongating Sand indoors.

**Storage information:**  
not sensitive to frost

**Base:**  
polyethylene

**Order information:**  
595012 | 45799 – Roll 15 m, 100 mm wide, 8 mm thick – pallet: 60 pieces; 12 boxes with 5 pieces



### WAKOL RS 5945 Edging Strips with Base, 50 mm



**Area of application:**  
Permanently elastic edge stripes with self-adhesive pedestal to be used if thicker levelling layers are required and before installation of WAKOL Z 515 Thin Screed.

**Storage information:**  
not sensitive to frost

**Base:**  
polyethylene

**Order information:**  
594503 | 41706 – Roll 25 m, 50 mm wide, 5 mm thick – pallet: 48 pieces; 12 boxes with 4 pieces



### WAKOL RS 5935 Edging Strips, 50 mm



**Area of application:**  
Self-adhesive, permanently elastic edge strips to be used if thicker levelling layers are required and before installation of WAKOL Z 515 Thin Screed.

**Storage information:**  
not sensitive to frost

**Base:**  
polyethylene

**Order information:**  
593502 | 34979 – Roll 25 m, 50 mm wide, 5 mm thick – pallet: 120 pieces; 12 boxes with 10 pieces



## WAKOL RS 5925 Edging Strips, 25 mm



**Area of application:**  
Self-adhesive, permanently elastic edging strips made of polyethylene for filling- and levelling work in medium layer thicknesses, ensuring edge clearance before decoupling work and ventilated timber substructures indoors.

**Storage information:**  
not sensitive to frost

**Base:**  
polyethylene

**Order information:**  
592502 | 45797 – Roll 25 m, 25 mm wide, 5 mm thick – pallet: 240 pieces; 12 boxes with 20 pieces



## WAKOL MS Special Roller



**Area of application:**  
Polyamide roller for applying WAKOL MS 330 Silane Primer when used as moisture barrier, for priming on strong absorbent subfloors, old subfloors and adhesive residues. Also suitable for applying WAKOL PS 275 Concrete Repair Primer.

**Base:**  
polyamide

**Order information:**  
597312 | 34999 – 2 pieces – pallet: 900 pieces; 10 boxes with 90 pieces



## WAKOL Levelling Pin



**Area of application:**  
Self-adhesive plastic pin with a scale from 10-100 mm before levelling with Wakol Levelling Compounds or WAKOL Z 515 Thin Screed.

**Consumption:**  
corresponding to the room size, room geometry and unevenness to be compensated

**Storage information:**  
not sensitive to frost

**Base:**  
synthetic material

**Order information:**  
598202 | 35009 – 50 pieces



## WAKOL Dust Reducer



**Area of application:**  
Extraction ring for dust reduction when working with levelling compounds, suitable for WAKOL Stirring Pail. WAKOL Dust Reducer will be delivered with a universal vacuum adapter.

**Base:**  
synthetic material

**Order information:**  
598302 | 37042 – 1 piece – pallet: 150 pieces; 150 boxes with 1 piece



## WAKOL Primer Roller, 11 mm



**Area of application:**  
Microfibre roller for easy applying of Wakol primers on absorbent and non-absorbent subfloors. Also suitable for applying Wakol Dispersion contact adhesives and Wakol fixations.

**Base:**  
microfibre

**Order information:**  
597503 | 34958 – 12 pcs with 1 bracket – pallet: 60 pieces



## WAKOL Double Paddle Mixer



**Area of application:**  
Double paddle mixer with diameter of 90 mm for the fast and homogeneous mixing of plasticised levelling compound and 2-component PU adhesives.


**Base:**  
steel

**Order information:**  
592315 | 41704 – 1 piece – pallet: 224 pieces





WAKOL Basket Stirrer



**Area of application:**  
Basket stirrer for mixing levelling compounds, with diameter of 120 mm and blade at basket ring. Equipped with M14 mounting for all current mixers.

**Base:**  
steel

**Order information:**  
592310 | 35004 – 1 piece



WAKOL Rakel with Distance Pins, 56 cm



**Area of application:**  
Scraper, 56 cm wide, equipped with distance pins for blade coating, also of higher layer thickness or fibre-reinforced levelling compounds. Can be used with and without trowel blades. Rakel blades notched on both sides are available as an accessory. The WAKOL Rakel Blade is made from hardened steel and available in the notch sizes TKB R2, TKB R3 and TKB R4.

**Base:**  
steel/synthetic material

**Order information:**  
598403 | 34987 – 1 pcs. Rakel 56 cm  
598031 | 34985 – TKB R2 56 cm – 1 box with 10 pieces  
598032 | 41384 – TKB R3 56 cm – 1 box with 10 pieces  
598033 | 41386 – TKB R4 56 cm – 1 box with 10 pieces



WAKOL Airing Roller



**Area of application:**  
Airing roller, 50 cm wide, spike length of 22 mm, with splash protection, for airing and improving flow properties of freshly applied self-flowing Wakol levelling compounds.

**Base:**  
steel/synthetic material

**Order information:**  
597403 | 42243 – 50 cm wide



WAKOL Rakel Blade



**Area of application:**  
Rakel blade notched on both sides, made from hardened steel, used in WAKOL Rakel or WAKOL Rakel with distance pins, 56 cm. WAKOL Rakel Blade is available in width of 56 cm and in the notch sizes TKB R2, TKB R3 and TKB R4.

**Base:**  
steel

**Order information:**  
598032 | 41384 – TKB R3 56 cm – 1 box with 10 pieces  
598033 | 41386 – TKB R4 56 cm – 1 box with 10 pieces  
598031 | 34985 – TKB R2 56 cm – 1 box with 10 pieces



WAKOL Rakel



**Area of application:**  
56-cm-wide Rakel for applying self-flowing Wakol levelling compounds. Rakel blades notched on both sides are available as an accessory. The WAKOL Rakel Blade is made from hardened steel and available in the notch sizes TKB R2, TKB R3 and TKB R4.

**Base:**  
steel/wood

**Order information:**  
598402 | 34986 – 1 pcs Rakel 56 cm  
598031 | 34985 – TKB R2 56 cm – 1 box with 10 pieces  
598032 | 41384 – TKB R3 56 cm – 1 box with 10 pieces  
598033 | 41386 – TKB R4 56 cm – 1 box with 10 pieces



WAKOL Master Trowel




**Area of application:**  
Ergonomic master trowel, 18 cm or 28 cm wide, for applying Wakol adhesives. Trowel blades notched on both sides, made from hardened steel, are available as an accessory. The WAKOL Trowel Blade is 18 cm or 28 cm wide. It is available in the notch sizes TKB A1, TKB A2, TKB B1 and TKB B2.

**Base:**  
steel/wood

**Order information:**  
597910 | 34997 – 28 cm – 1 box with 10 pieces  
597903 | 34998 – 18 cm – 1 box with 10 pieces



WAKOL Trowel Blade



**Area of application:**  
Trowel blade notched on both sides, made from hardened steel, used in WAKOL Master Trowel. WAKOL Trowel Blade is available in width of 18 cm or 28 cm and in the notch sizes TKB A1, TKB A2, TKB B1 and TKB B2.

**Base:**  
steel

<b>Order information:</b>	
598010	34908 – TKB A1 28 cm – 1 box with 10 pieces
598007	34909 – TKB A1 18 cm – 1 box with 10 pieces
598011	34906 – TKB A2 28 cm – 1 box with 10 pieces
598003	34907 – TKB A2 18 cm – 1 box with 10 pieces
598012	34904 – TKB B1 28 cm – 1 box with 10 pieces
598002	34905 – TKB B1 18 cm – 1 box with 10 pieces
598014	34902 – TKB B2 28 cm – 1 box with 10 pieces
598006	34903 – TKB B2 18 cm – 1 box with 10 pieces



WAKOL Speciality Trowel 5



**Area of application:**  
Special notch to form a moisture barrier on unheated cement screeds up to 4 CM% resp. 85 % corresponding relative humidity for laying parquets (all types of parquets with tongue and groove joint) with WAKOL MS 262 Parquet Adhesive, firm-elastic, WAKOL MS 260 Parquet Adhesive, firm-elastic, WAKOL MS 258 Parquet Adhesive, firm-elastic, WAKOL MS 239 Parquet Adhesive, elastic, WAKOL MS 232 Parquet Adhesive, elastic, WAKOL MS 230 Parquet Adhesive, elastic or WAKOL MS 228 Ready-to-lay Parquet Adhesive, elastic.  
Alternatively, the WAKOL Speciality Trowel Blade 5, 18 cm wide, for use in WAKOL Master Trowel is also available.

**Base:**  
steel/aluminium

<b>Order information:</b>	
598602	31471 – 1 pcs. Speciality Trowel 18 cm
598021	34968 – Speciality Trowel Blade 18 cm – 1 box with 10 pieces



WAKOL Parquet Notched Trowel



**Area of application:**  
Notched trowel according to TKB for applying Wakol parquet adhesives. WAKOL Parquet Notched Trowels are available in notch sizes TKB B3, TKB B5, TKB B11, TKB B13 and TKB B15 with 18 cm width.

**Base:**  
steel/wood

<b>Order information:</b>	
598502	34992 – TKB B3 18 cm – 1 box with 10 pieces
598503	34991 – TKB B5 18 cm – 1 box with 10 pieces
598504	34995 – TKB B11 18 cm – 1 box with 10 pieces
598505	34994 – TKB B13 18 cm – 1 box with 10 pieces
598506	34993 – TKB B15 18 cm – 1 box with 10 pieces



WAKOL Speciality Trowel Blade 5




**Area of application:**  
Special trowel blade, 18 cm wide, used in WAKOL Master Trowel 18 cm to form a moisture barrier on unheated cement screeds up to 4 CM% resp. 85 % corresponding relative humidity for laying parquets (all types of parquets with tongue and groove joint) with WAKOL MS 262 Parquet Adhesive, firm-elastic, WAKOL MS 260 Parquet Adhesive, firm-elastic, WAKOL MS 258 Parquet Adhesive, firm-elastic, WAKOL MS 239 Parquet Adhesive, elastic, WAKOL MS 232 Parquet Adhesive, elastic, WAKOL MS 230 Parquet Adhesive, elastic or WAKOL MS 228 Ready-to-lay Parquet Adhesive, elastic.  
Alternatively the WAKOL Speciality Trowel 5, 18 cm wide, can also be used.

**Base:**  
steel

<b>Order information:</b>	
598021	34968 – Speciality Trowel Blade 18 cm – 1 box with 10 pieces
598602	31471 – 1 pcs. Speciality Trowel 18 cm



WAKOL Notched Trowel



**Area of application:**  
Notched trowel according to TKB for applying Wakol dispersion adhesives. WAKOL Notched Trowels are available in notch sizes TKB A1 and TKB A2 with 25 cm width and in notch sizes TKB B1 and TKB B2 with 18 cm width.

**Base:**  
steel/wood

<b>Order information:</b>	
598511	34901 – TKB A1 25 cm – 1 box with 10 pieces
598512	34900 – TKB A2 25 cm – 1 box with 10 pieces
598513	42244 – TKB B1 18 cm – 1 box with 10 pieces
598514	42245 – TKB B2 18 cm – 1 box with 10 pieces



WAKOL Replaceable Nozzle



**Area of application:**  
Replaceable nozzles, 200 mm and 400 mm wide, for use in WAKOL Applicator 90, Parkett-X-Press, Parkett-X-Press Air and Lite-X-Press. Appropriate guide brackets in widths of 200 mm and 400 mm are also available.

<b>Order information:</b>	
597605	34915 – 200-11-3,5 – 1 box with 7 pieces
597604	34914 – 200-18-3,5 – 1 box with 7 pieces
597625	34913 – 414-25-3,5 – 1 box with 5 pieces
597624	34912 – 414-40-3,5 – 1 box with 5 pieces
597633	35018 – 1 pc. Guide Bracket 200 mm
597635	35017 – 1 pc. Guide Bracket 414 mm





WAKOL Applicator 90



**Area of application:**  
Battery-operated sausage gun for applying Wakol adhesives in tubular bags (Ø 88 mm / 4.200 ml), e.g. WAKOL MS 292 Parquet Adhesive, shear-resistant, WAKOL MS 262 Parquet Adhesive, firm-elastic or WAKOL MS 232 Parquet Adhesive, elastic. The WAKOL Applicator 90 comes with a 200 mm distributor head for mounting WAKOL Replaceable Nozzles, a quick-charger and two 18 V rechargeable batteries in the case including a stand.

**Weight:**  
WAKOL Applicator 90 approx. 5.8 kg, incl. case and accessories approx. 14 kg

**Delivery:**  
WAKOL Applicator 90, 200 distributor head, two 18 V li-ion batteries, quick-charger with charging indicator, transport case with stand

**Drive:**  
controllable, 9-stage

**Holder:**  
Aluminium tube for tubular bags, diameter 90 mm

**Charging station:**  
Input: 110 - 240V ~ 50/60Hz 60W  
Output: DC 18V A 3.0A

**Safety:**  
CE certified

**Order information:**  
597632 | 35037 – 1 piece  
597639 | 35040 – 1 pc. rechargeable battery 18 V - 1,5 AH  
597637 | 34971 – 1 pc. quick-charger

WAKOL Applicator 50



**Area of application:**  
Battery-operated sausage gun for applying Wakol adhesives in tubular bags (Ø 49 mm/up to 600 ml) and cartridges, e.g. WAKOL MS 262 Parquet Adhesive, firm-elastic, WAKOL MS 232 Parquet Adhesive, elastic, WAKOL MS 246 StarMonti or WAKOL MS 245 Montinator. The WAKOL Applicator 50 comes with a quick-charger and two 10.8 V rechargeable batteries in the case.

**Weight:**  
WAKOL Applicator 50 approx. 2,3 kg; incl. case and accessories approx. 5.3 kg

**Delivery:**  
WAKOL Applicator 50, 2 Li-Ion batteries with 10.8 V, quick-charger with load indicator, carriage case

**Drive:**  
controllable, up to 330 mm/min, automatic return

**Holder:**  
Compound holder 600 ml for tabular bags and cartridges, diameter 50 mm

**Charging station:**  
Input: 100 - 240V ~ 50/60 Hz 30W  
Output: DC 10.8 A 2A

**Safety:**  
CE certified

**Order information:**  
597603 | 35038 – 1 piece

WAKOL Manual Applicator 400



**Area of application:**  
Manual applicator gun for application of Wakol sausage and cartridge adhesives up to 400 ml filling amount. WAKOL Manual Applicator 400 has an ergonomically designed handle and an optimised transmission for easy mounting adhesive application, such as WAKOL MS 246 StarMonti or WAKOL MS 245 Montinator.

**Weight:**  
WAKOL Manual Applicator 400 approx. 0.814 kg

**Holder:**  
Compound holder 400 ml for tabular bags and cartridges, diameter 40 mm

**Order information:**  
597679 | 36017 – 1 piece

WAKOL Proportioning Pail



**Area of application:**  
Transparent, graduated proportioning pail (11 l) for easily measuring out water and WAKOL S 25 Elongating Sand. Lid is separately available.

**Order information:**  
590203 | 34923 – 1 pcs. Pail – pallet: 250 pieces  
590204 | 35021 – 1 pcs. Lid

WAKOL Stirring Pail



**Area of application:**  
Stirring pail (30 l) with firm rim and handle shell for mixing all Wakol levelling compounds.

**Order information:**  
590102 | 35039 – 1 piece – pallet: 240 pieces

WAKOL Softshell-Jacket



**Area of application:**  
Water-repellent jacket made of 92 % polyester/ 8 % elastane in modern form fitted with two angled side pockets with zipper, two inner pockets and elastic seam cord. Breathable, especially hard-wearing.

**Colour:**  
blue

**Size:**  
S-3XL

**Order information:**  
591232 | 41375 – S  
591233 | 34937 – M  
591234 | 34938 – L  
591235 | 36007 – XL  
591236 | 41376 – XXL  
591237 | 41377 – 3XL

WAKOL Work Jacket



**Area of application:**  
Jacket made of 65 % polyester/ 35 % cotton in extended blouson form fitted with convenient snap fasteners, also on the sleeves and with comfortable pleated back. Many pockets – two breast pockets with flaps, two side pockets – make the jacket a practical item of clothing. Breathable, especially hard-wearing.

**Colour:**  
black/grey

**Size:**  
42-64; 90-110; 24-29

**Order information:**  
591212 | 34957 – 1 piece

WAKOL Polo-Shirt



**Area of application:**  
Fashionable polo-shirt made of 100 % cotton. Neckband, colour-contrasting button strip.

**Colour:**  
blue

**Size:**  
S-XL

**Order information:**  
591619 | 36012 – S  
591618 | 36011 – M  
591617 | 36010 – L  
591616 | 36009 – XL  
591615 | 36027 – XXL  
591614 | 36028 – 3XL

WAKOL Waistband Trousers



**Area of application:**  
High-quality waistband trousers made of 65 % polyester/ 35 % cotton with knee area reinforced due to additionally fitted knee pockets. Many pockets – one pouch and two back pockets with flaps and snap fasteners – make the trousers a practical item of clothing. Breathable, especially hard-wearing.

**Colour:**  
black/ grey

**Size:**  
42-62; 98-102; 24-27

**Order information:**  
591128 | 34956 – 44  
591127 | 34955 – 46  
591126 | 34954 – 48  
591125 | 34953 – 50  
591124 | 34952 – 52  
591123 | 34951 – 54  
591122 | 34950 – 56  
591121 | 34949 – special sizes

WAKOL T-Shirt



**Area of application:**  
Hard-wearing T-Shirt made of 100 % ring-spun cotton, with ribbed collar, shoulder-to-shoulder neckband and double seam on sleeves and waistband for additional stability. The comfortable, soft material structure offers a pleasant wearing comfort. Logo print on breast and back.

**Colour:**  
blue

**Size:**  
M-2XL

**Order information:**  
591319 | 36008 – S  
591318 | 34929 – M  
591317 | 34930 – L  
591316 | 34928 – XL  
591315 | 34927 – XXL

WAKOL Dungarees



**Area of application:**  
Dungarees made of 65 % polyester/ 35 % cotton for the highest quality demands. Especially hard-wearing, breathable, for good body temperature. 2 fitted pouch pockets made of Cordura, on right double folding rule pocket, reflective piping on pocket openings and flaps, on left thigh pocket with flap and snap fasteners, fitted mobile phone pocket, double bib pocket, reinforced rear pocket. Reverse of fabric slightly roughened, very breathable, especially hard-wearing.

**Colour:**  
black/grey

**Size:**  
42-64; 90-110; 24-29

**Order information:**  
591002 | 41580 – 44  
591003 | 42023 – 46  
591004 | 34921 – 48  
591005 | 34920 – 50  
591006 | 34919 – 52  
591007 | 34918 – 54  
591008 | 34917 – 56  
591001 | 34916 – special sizes



Direct installation of elastic and textile floorings  
on standardised or renovated subfloors

<div>Subfloors</div> <div>Flooring</div>	Cement screeds (CT) with sufficient smooth and level surface	Calcium sulfate screeds (CA) with sufficient smooth and level surface	Chipboards according to DIN EN 312 (P4 up to P7), these must be fully leveled with plasticised levelling compound or filled normally	Newly levelled subfloors with Wakol levelling compounds	Newly levelled subfloors with Wakol levelling compounds plastified with WAKOL D 3060 Plastification Additive	Gypsum fibre boards, primed with Wakol primers	WAKOL TS 102 Footfall Soundproofing Mat, 2 mm completely cover bonded WAKOL TS 103 Footfall Soundproofing Mat 3 mm completely cover bonded WAKOL TS 112 Footfall Soundproofing Mat 2 mm completely cover bonded
Specifies	Prime with D 3004 1:2 / D 3003, not suitable for wheelchairs	Prime with D 3004 1:2 / D 3003, not suitable for wheelchairs	Smooth joints and screw holes with A 830 plastified with D 3060			not suitable for wheelchairs	Please note technical information TS 102, TS 103 and TS 112
Textile flooring with TR-backing, fleece backing or latex backing	D 3270      D 3311 D 3304      D 3312 D 3307      D 3360 D 3308 D 3310	D 3270      D 3311 D 3304      D 3312 D 3307      D 3360 D 3308 D 3310	D 3270      D 3311 D 3304      D 3312 D 3307      D 3360 D 3308 D 3310	D 3270      D 3311 D 3304      D 3312 D 3307      D 3360 D 3308 D 3310	D 3270      D 3311 D 3304      D 3312 D 3307      D 3360 D 3308 D 3310	D 3270      D 3311 D 3304      D 3312 D 3307      D 3360 D 3308 D 3310	D 3270      D 3311 D 3304      D 3312 D 3307      D 3360 D 3308 D 3310
Textile flooring with synthetic fleece backing or latex backing	D 3304      D 3311 D 3307      D 3312 D 3308      D 3360 D 3310	D 3304      D 3311 D 3307      D 3312 D 3308      D 3360 D 3310	D 3304      D 3311 D 3307      D 3312 D 3308      D 3360 D 3310	D 3304      D 3311 D 3307      D 3312 D 3308      D 3360 D 3310	D 3304      D 3311 D 3307      D 3312 D 3308      D 3360 D 3310	D 3304      D 3311 D 3307      D 3312 D 3308      D 3360 D 3310	D 3304      D 3311 D 3307      D 3312 D 3308      D 3360 D 3310
Textile flooring with jute backing Textile flooring, woven	D 3307 D 3320 D 3360	D 3307 D 3320 D 3360	D 3307 D 3320 D 3360	D 3307 D 3320 D 3360	D 3320 D 3360		D 3307 D 3320 D 3360
Textile flooring with PVC-backing	D 3304      D 3312 D 3308      D 3360 D 3310      MS 550 D 3311      MS 552	D 3304      D 3312 D 3308      D 3360 D 3310      MS 550 D 3311      MS 552	D 3304      D 3360 D 3308      MS 550 D 3310      MS 552 D 3311 D 3312	D 3304      D 3360 D 3308      MS 550 D 3310      MS 552 D 3311 D 3312	D 3304      D 3360 D 3308      MS 550 D 3310      MS 552 D 3311 D 3312	D 3304      D 3360 D 3308      MS 550 D 3310      MS 552 D 3311 D 3312	D 3304      D 3360 D 3308      MS 550 D 3310      MS 552 D 3311 D 3312
Needle fleece flooring			D 3304      MS 550 D 3311      MS 552 D 3318 D 3360	D 3304      MS 550 D 3311      MS 552 D 3318 D 3360	D 3304      MS 550 D 3311      MS 552 D 3318 D 3360		D 3304*1      MS 550*1 D 3311*1      MS 552*1 D 3318*1 D 3360*1
Linoleum with jute woven backing			D 3125      D 3319 D 3313      D 3320 D 3307      D 3360 D 3316      MS 550 D 3317      MS 552 D 3318      PU 270	D 3125      D 3319 D 3307      D 3320 D 3313      D 3360 D 3316      MS 550 D 3317      MS 552 D 3318      PU 270	D 3125      D 3319 D 3307      D 3320 D 3313      D 3360 D 3316      MS 550 D 3317      MS 552 D 3318      PU 270		D 3125*1      D 3319*1 D 3307*1      D 3320*1 D 3313*1      D 3360*1 D 3316*1      MS 550*1 D 3317*1      MS 552*1 D 3318*1      PU 270*1
PVC flooring, homogeneous			D 3125      D 3319 D 3313      D 3320 D 3320      D 3360 D 3316      MS 550 D 3317      MS 552 D 3318      PU 270	D 3125      D 3319 D 3307      D 3320 D 3313      D 3360 D 3316      MS 550 D 3317      MS 552 D 3318      PU 270	D 3125      D 3319 D 3307      D 3320 D 3313      D 3360 D 3316      MS 550 D 3317      MS 552 D 3318      PU 270		D 3125*1      D 3320*1 D 3307*1      D 3360*1 D 3313*1      MS 550*1 D 3316*1      MS 552*1 D 3317*1      PU 270*1 D 3318*1
PVC bond flooring with polyester fleece backing and CT flooring			D 3125      D 3320 D 3307      D 3360 D 3313      MS 550 D 3316      MS 552 D 3317      PU 270 D 3318 D 3319	D 3125      D 3320 D 3307      D 3330 D 3313      D 3360 D 3316      MS 550 D 3317      MS 552 D 3318      PU 270 D 3319	D 3125      D 3320 D 3307      D 3360 D 3313      MS 550 D 3316      MS 552 D 3317      PU 270 D 3318 D 3319		D 3125*1      D 3320*1 D 3307*1      D 3360*1 D 3313*1      MS 550*1 D 3316*1      MS 552*1 D 3317*1      PU 270*1 D 3318*1 D 3319*1
LVT flooring			MS 550 MS 552 PU 270	D 3317      D 3320 D 3318      MS 550 D 3360      MS 552 PU 270	MS 550 MS 552 PU 270		MS 550*2 MS 552*2 PU 270*2
PVC-free flooring PU or PO base or with fleece backed			D 3313*3 D 3318*3 MS 550*3 MS 552*3	D 3313*3 D 3318*3 MS 550*3 MS 552*3	MS 550*3 MS 552*3 PU 270*3		MS 550*3 MS 552*3 PU 270*3

The applicable standards and fact sheets must be heeded with all laying operations as well as manufacturer's instructions.

Please note:

- \*1 Pretreat surface with WAKOL A 830 Anhydrite Levelling Compound or WAKOL Z 615 Levelling Compound, dust-reduced plastified with WAKOL D 3060 Plastification Additive
- \*2 Pretreat surface with WAKOL Z 615 Levelling Compound, dust-reduced plastified with WAKOL D 3060 Plastification Additive

\*3 Please observe adhesive recommendation of flooring manufacturer or consult Wakol technical support

All mentioned products are very low in emissions

Subfloor preparation of non suitable subfloors for direct bonding of elastic and textile flooring according to DIN 18365

Subfloors	Preparation	Prepare	Primer Dilution	Drying time	Bonding of reinforce- ment / decoupling	Reinforcement / decoupling	Primer Dilution	Drying time	Levelling
Cement screeds (CT), Concrete slabs		Grind and vacuum RS 5925, RS 5935 or RS 5945	D 3003 or D 3004 1:2 with water	when suitable for walking					A 830 A 885 Z 610 Z 615 Z 625 Z 630 Z 635 Z 675 Z 680 Z 715 Z 515
Calcium sulfate screeds (CA)		Grind and vacuum RS 5925, RS 5935 or RS 5945	D 3003 or D 3004 1:2 with water	approx. 1 hour, when suitable for walking in combination with A 830 and A 885					
Magnesite screeds (MA)		Grind and vacuum RS 5925, RS 5935 or RS 5945	PU 280 PU 235 MS 330	approx. 1 hour approx. 4-6 hours approx. 1 hour			D 3045	approx. 1 hour	
Mastic asphalt screeds (AS)		Grind and vacuum RS 5925, RS 5935 or RS 5945	D 3004 1:1 with water or D 3045	approx. 30-60 minutes					
Terrazzo, tiles		Cleaning with R 4515, RS 5925, RS 5935 or RS 5945	D 3004 undiluted or D 3045	approx. 30-60 minutes					
Gypsum fibre boards		Grind and vacuum RS 5925, RS 5935 or RS 5945	D 3003 or D 3004 1:2 with water	approx. 1 hour					A 830*1    Z 615*1 A 885*1    Z 625*1 Z 610 *1    Z 630*1
Old adhesive remnants on standardised subfloors, nor as waterproof		Grind and vacuum RS 5925, RS 5935 or RS 5945	PU 280 PU 235 MS 330	approx. 1 hour approx. 4-6 hours approx. 1 hour			D 3045	approx. 1 hour	A 830 A 885 Z 610 Z 615 Z 625 Z 630 Z 635 Z 675 Z 680 Z 715 Z 515
Cement screeds (CT) with to high residual humidity up to 6 CM% / 98 % KRL without underfloor heating, up to 3 CM% / 85 % KRL with underfloor heating, concrete with to high residual humidity up to 7.5 % / 98 % KRL by weight		Grind and vacuum RS 5925, RS 5935 or RS 5945	PU 280 2-fold layer PU 235 2-fold layer	approx. 1 hour per layer approx. 4-6 hours per layer					
Cement screeds (CT) with to high residual humidity up to 5 CM% / 95 % KRL without underfloor heating, up to 3 CM% / 85 % KRL with underfloor heating, concrete with to high residual humidity up to 7 % / 95 % KRL by weight		Grind and vacuum RS 5925, RS 5935 or RS 5945	MS 330	approx. 1 hour					
Cement screeds (CT), concrete with insufficient surface stability		Grind and vacuum RS 5925, RS 5935 or RS 5945	PU 280 *2 PU 235 *2 MS 330 *2	approx. 1 hour approx. 4-6 hours per layer approx. 1 hour					
Cement screeds (CT) with to high residual humidity up to 5 CM% / 95 % KRL without underfloor heating, up to 3 CM% / 85 % KRL with underfloor heating		Grind and vacuum RS 5925, RS 5935 or RS 5945	D 3080 1:1 with water then D 3080 undiluted	at least. 30 minutes  at least. 120 minutes					Z 610    Z 675 Z 615    Z 680 Z 625    Z 715 Z 630    Z 515 Z 635
Cement screeds (CT), concrete, calcium sulfate screeds (CA), magnesite sceeds (MA) or mastic asphalt screeds (AS) sufficient load-bearing but with cracks or not homogeneous (different pavings)		Grind and vacuum RS 5925, RS 5935 or RS 5945	PU 280 PU 235 MS 330 *3	approx. 1 hour approx. 4-6 hours approx. 1 hour	MS 290    PU 385 MS 292    PU 215 *E MS 299    PU 216 *E PU 210    PU 220 *E PU 225	EM 140 *2    RP 704 *2 RP 104 *2    RP 709 *2 RP 107 *2    RP 715 *2 RP 109 *2 RP 115 *2			A 830    Z 630 Z 610    Z 515 Z 615 Z 625
Old, finished floors, permanent existing only tiles, wood planks, linoleum, parquet		Cleaning tiles with R 4515, sand entire surface RS 5925, RS 5935 or RS 5945			MS 290    PU 225 MS 292    PU 385 MS 299    PU 215 *E PU 210    PU 216 *E PU 225    PU 220 *E	EM 140    RP 115 RP 104    RP 704 RP 107    RP 709 RP 109    RP 715			A 830 Z 610 Z 615 Z 625 Z 630
Old, finished floors, permanent existing only tiles, wood planks, linoleum, parquet		Cleaning tiles with R 4515, sand entire surface							D 3060 +    Z 645 Z 610 Z 615 Z 625 Z 630 Z 640
Installation lines to be levelled, levelling/filling of wooden floorboards and wooden beam compartments, levelling of areas with limited static load-bearing capacity (according to the planner's specifications)		Set up screed edge strips, lay out suitable foil for installation on separating layer, apply primer or bonding slurry to the subfloor, WAKOL Z 590 Light Screed		24 hours		AR 150 levelled with Z 640/Z645 mixed with D 3060			Z 515 Z 610 Z 615 Z 625 Z 630 A 830

The applicable standards and fact sheets must be heeded with all laying operations.

Please note:  
\*1 If levelling is necessary  
\*2 Depending on subfloor stability, in case of doubt please consult Wakol technical support  
\*3 Direct installation only with MS Parquet Adhesives  
  
\*E All mentioned products are very low in emissions, except for \*E

Direct installation of parquet on standardised subfloors

<div>Subfloors</div> <div>Flooring</div>	Cement screeds (CT)		Calcium sulfate screeds (CA)		Magnesia screeds (MA)		Mastic asphalt screeds (AS)		Wood-based material boards Chipboards according to DIN EN 312 (P4 up to P7) OSB according to DIN EN 300 (OSB/2 up to OSB/4)		Gypsum fibre boards, as far as parquet type is recommended for direct bonding by manufacturer	
Specifics							The hardness of the cast asphalt must be suitable for cementing parquets					
Prepare	Grind and vacuum D 3055 *7		Grind and vacuum D 3055 *7		Grind and vacuum		Vacuum		Vacuum		Vacuum D 3055 *7	
Mosaic parquet DIN EN 13488, edge lamella parquet DIN EN 14761	D 1640 *5 D 1690 *5 MS 230 *5 MS 232 *5 MS 239 *5 MS 258 *5 MS 260 *5 MS 261 *5 MS 262 *5 MS 265 *5	MS 290 MS 292 MS 299 PU 210 PU 225 PU 385 *1 PU 215 *E PU 216 *E PU 220 *E	MS 230 *5 MS 232 *5 MS 239 *5 MS 258 *5 MS 260 *5 MS 261 *5 MS 262 *5 MS 265 *5 MS 290 MS 292	MS 299 PU 210 PU 225 PU 385 *1 PU 215 *E PU 216 *E PU 220 *E	MS 230 *5 MS 232 *5 MS 239 *5 MS 258 *5 MS 260 *5 MS 261 *5 MS 262 *5 MS 265 *5 MS 290 MS 292	MS 299 PU 210 PU 225 PU 385 *1 PU 215 *E PU 216 *E PU 220 *E	MS 230 *3 *5 MS 232 *3 *5 MS 239 *3 *5 MS 258 *3 *5 MS 260 *3 *5 MS 261 *3 *5 MS 262 *3 *5 MS 265 *5 MS 290 MS 292	MS 299 PU 210 PU 225 PU 385 *1*3 PU 215 *E PU 216 *E PU 220 *E	MS 230 *5 MS 232 *5 MS 239 *5 MS 258 *5 MS 260 *5 MS 261 *5 MS 262 *5 MS 265 *5 MS 290 MS 292	MS 299 PU 210 PU 225 PU 385 *1 PU 215 *E PU 216 *E PU 220 *E	MS 230 *5 MS 232 *5 MS 239 *5 MS 258 *5 MS 260 *5 MS 261 *5 MS 262 *5 MS 265 *5 MS 290 MS 292	MS 299 PU 210 PU 225 PU 385 *1 PU 215 *E PU 216 *E PU 220 *E
Strip parquet DIN EN 13226	D 1640 *2 D 1690 *5 MS 230 *6 MS 232 *6 MS 239 *6 MS 258 MS 260 MS 261 MS 262 MS 265	MS 290 MS 292 MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 230 *6 MS 232 *6 MS 239 *6 MS 258 MS 260 MS 261 MS 262 MS 265 MS 290 MS 292	MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 230 *6 MS 232 *6 MS 239 *6 MS 258 MS 260 MS 261 MS 262 MS 265 MS 290 MS 292	MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 230 *3 *6 MS 232 *3 *6 MS 239 *3 *6 MS 258 *3 MS 260 *3 MS 261 *3 MS 262 *3 MS 265 MS 290 MS 292	MS 299 PU 210 PU 225 PU 385 *3 PU 215 *E PU 216 *E PU 220 *E	MS 230 *6 MS 232 *6 MS 239 *6 MS 258 MS 260 MS 261 MS 262 MS 265 MS 290 MS 292	MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 230 *6 MS 232 *6 MS 239 *6 MS 258 MS 260 MS 261 MS 262 MS 265 MS 290 MS 292	MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E
Solid parquet 10 mm DIN EN 13227	MS 260 MS 261 MS 262 MS 265 MS 290 MS 292 MS 299	PU 210 PU 225 PU 215 *E PU 216 *E PU 220 *E	MS 260 MS 261 MS 262 MS 265 MS 290 MS 292 MS 299	PU 210 PU 225 PU 215 *E PU 216 *E PU 220 *E	MS 260 MS 261 MS 262 MS 265 MS 290 MS 292 MS 299	PU 210 PU 225 PU 215 *E PU 216 *E PU 220 *E	MS 260 *3 MS 261 *3 MS 262 *3 MS 265 MS 290 MS 292 MS 299	PU 210 PU 225 PU 215 *E PU 216 *E PU 220 *E	MS 260 MS 261 MS 262 MS 265 MS 290 MS 292 MS 299	PU 210 PU 225 PU 215 *E PU 216 *E PU 220 *E		
Multi-layered parquet DIN EN 13489	D 1640 D 1690 MS 228 MS 230 MS 232 MS 239 MS 258 MS 260 MS 261 MS 262	MS 265 MS 290 MS 292 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 228 MS 230 MS 232 MS 239 MS 258 MS 260 MS 261 MS 262 MS 265 MS 290	MS 292 MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 228 MS 230 MS 232 MS 239 MS 258 MS 260 MS 261 MS 262 MS 265 MS 290	MS 292 MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 230 *3 MS 232 *3 MS 239 *3 MS 258 *3 MS 260 *3 MS 261 *3 MS 262 *3 MS 265 MS 290 MS 292	MS 299 PU 210 PU 225 PU 385 *3 PU 215 *E PU 216 *E PU 220 *E	MS 228 MS 230 MS 232 MS 239 MS 258 MS 260 MS 261 MS 262 MS 265 MS 290	MS 292 MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 228 MS 230 MS 232 MS 239 MS 258 MS 260 MS 261 MS 262 MS 265 MS 290	MS 292 MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E
Multi-layered parquet DIN EN 13489, 3-layer	MS 260 *4 MS 261 *4 MS 262 *4 MS 265 *4 MS 290 MS 292 MS 299	PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 260 *4 MS 261 *4 MS 262 *4 MS 265 *4 MS 290 MS 292 MS 299	PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 260 *4 MS 261 *4 MS 262 *4 MS 265 *4 MS 290 MS 292 MS 299	PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 260 *3 *4 MS 261 *3 *4 MS 262 *3 *4 MS 265 MS 290 MS 292 MS 299	PU 210 PU 225 PU 385 *3 PU 215 *E PU 216 *E PU 220 *E	MS 260 *4 MS 261 *4 MS 262 *4 MS 265 *4 MS 290 MS 292 MS 299	PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 260 *4 MS 261 *4 MS 262 *4 MS 265 *4 MS 290 MS 292 MS 299	PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E
Solid plank DIN EN 13226 in the system with WAKOL TS 102, WAKOL TS 103 or WAKOL TS 112	MS 260 MS 261 MS 262 MS 265 MS 290 MS 292 MS 299	PU 210 PU 225 PU 385 PU 216 *E	MS 260 MS 261 MS 262 MS 265 MS 290 MS 292 MS 299	PU 210 PU 225 PU 385 PU 216 *E	MS 260 MS 261 MS 262 MS 265 MS 290 MS 292 MS 299	PU 210 PU 225 PU 385 PU 216 *E	MS 260 *3 MS 261 *3 MS 262 *3 MS 265 MS 290 MS 292 MS 299	PU 210 PU 225 PU 385 *3 PU 216 *E	MS 260 MS 261 MS 262 MS 265 MS 290 MS 292 MS 299	PU 210 PU 225 PU 216 *E PU 385		

The applicable standards and fact sheets must be heeded with all laying operations.

Please note:

- \*1 Only on edge lamella from 22 mm in width
- \*2 Only oak wood
- \*3 Only in combination with WAKOL PU 280 Polyurethane Primer, WAKOL PU 235 Polyurethane Primer or WAKOL MS 330 Silane Primer
- \*4 Up to max. 18 cm in width, oak wood up to max. 20 cm in width

- \*5 On edge lamella parquet from 16 mm in width, max. 200 mm in length
- \*6 Max. 80 mm in width, 600 mm in length
- \*7 If necessary
- \*E All mentioned products are very low in emissions, except for \*E



Direct installation of parquet on renovated subfloors

<div>Subfloors</div> <div>Flooring</div>	Sufficient level and firmly attached terrazzo-, stone tiles, wood planks and parquet floors	Newly levelled subfloors with Wakol levelling compounds suitable for parquet laying	Newly levelled subfloors with cement based Wakol levelling compounds plastified with WAKOL D 3060 Plastification Additive	WAKOL PU 235 Polyurethane Primer WAKOL PU 280 Polyurethane Primer WAKOL MS 330 Silane Primer *5	WAKOL TS 102 Footfall Soundproofing Mat, 2 mm completely cover bonded WAKOL TS 103 Footfall Soundproofing Mat, 3 mm completely cover bonded WAKOL TS 112 Footfall Soundproofing Mat, 2 mm completely cover bonded	WAKOL EM 140 Uncoupling Fleece WAKOL RP 104 Decoupling Sheet, 4 mm WAKOL RP 107 Decoupling Sheet, 4 mm WAKOL RP 109 Decoupling Sheet, 9 mm WAKOL RP 115 Decoupling Sheet, 15 mm WAKOL RP 704 Project Decoupling Sheet, 4 mm WAKOL RP 707 Project Decoupling Sheet, 7 mm WAKOL RP 709 Project Decoupling Sheet, 9 mm WAKOL RP 715 Project Decoupling Sheet, 15 mm
Specifics				within 72 hours	Please note technical information TS 102, TS 103 and TS 112	
Prepare	Cleaning tiles with R 4515, sand entire surface					
Mosaic parquet DIN EN 13488, edge lamella parquet DIN EN 14761	MS 230 *6 MS 232 *6 MS 239 *6 MS 258 *6 MS 260 *6 MS 261 *6 MS 262 *6 MS 265 *6 MS 290	MS 292 MS 299 PU 210 PU 225 PU 385 *4 PU 215 *E PU 216 *E PU 220 *E	D 1640 *6 D 1690 *6 MS 230 *6 MS 232 *6 MS 239 *6 MS 258 *6 MS 260 *6 MS 261 *6 MS 262 *6 MS 265 *6	MS 290 MS 292 MS 299 PU 210 PU 225 PU 385 *4 PU 215 *E PU 216 *E PU 220 *E	MS 230 *6 MS 232 *6 MS 239 *6 MS 258 *6 MS 260 *6 MS 261 *6 MS 262 *6 MS 265 *6 MS 290	MS 292 MS 299 PU 210 PU 225 PU 385 *4 PU 215 *E PU 216 *E PU 220 *E
Strip parquet DIN EN 13226	MS 230 *2 MS 232 *2 MS 239 *2 MS 258 MS 260 MS 261 MS 262 MS 265 MS 290	MS 292 MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	D 1640 *1 D 1690 *1 MS 230 *2 MS 232 *2 MS 239 *2 MS 258 MS 260 MS 261 MS 262 MS 265	MS 290 MS 292 MS 299 PU 210 PU 225 PU 385 PU 215*E PU 216 *E PU 220 *E	MS 230 *2 MS 232 *2 MS 239 *2 MS 258 MS 260 MS 261 MS 262 MS 265 MS 290	MS 292 MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E
Solid parquet 10mm DIN EN 13227	MS 260 MS 261 MS 262 MS 265 MS 290 MS 292	MS 299 PU 210 PU 225 PU 215 *E PU 216 *E PU 220 *E	MS 260 MS 261 MS 262 MS 265 MS 290 MS 292	MS 299 PU 210 PU 225 PU 215 *E PU 216 *E PU 220 *E	MS 260 MS 261 MS 262 MS 265 MS 290 MS 292	MS 299 PU 210 PU 225 PU 215 *E PU 216 *E PU 220 *E
Multi-layered parquet DIN EN 13489, 2-layer	MS 228 MS 230 MS 232 MS 239 MS 258 MS 260 MS 261 MS 262 MS 265 MS 290	MS 292 MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	D 1640 D 1690 MS 228 MS 230 MS 232 MS 239 MS 258 MS 260 MS 261 MS 262	MS 265 MS 290 MS 292 MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 290 MS 239 MS 258 PU 210 PU 225 PU 215 *E PU 216 *E PU 220 *E	MS 292 MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E
Multi-layered parquet DIN EN 13489, 3-layer	MS 228 MS 230 MS 232 MS 239 MS 258 MS 260 MS 261 MS 262 MS 265	MS 290 MS 292 MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 228 MS 230 MS 232 MS 239 MS 258 MS 260 MS 261 MS 262 MS 265	MS 290 MS 292 MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 228 MS 230 MS 232 MS 260 MS 261 MS 265 MS 239 MS 258	MS 290 MS 292 MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E
Solid plank DIN EN 13226	MS 260 *3 MS 261 *3 MS 262 *3 MS 265 *3 MS 290 MS 292 MS 299	PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 260 *3 MS 261 *3 MS 262 *3 MS 265 *3 MS 290 MS 292 MS 299	PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	MS 260 *3 MS 261 *3 MS 262 *3 MS 265 *3 MS 290 MS 292 MS 299	PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E
Wood block RE/WE DIN EN 68702 in the system with WAKOL TS 102, WAKOL TS 103 or WAKOL TS 112					MS 260 MS 261 MS 262 MS 265 MS 290	MS 292 MS 299 PU 210 PU 225 PU 385

The applicable standards and fact sheets must be heeded with all laying operations.

Please note:

- \*1 Only oak wood
- \*2 Max. 80 mm in width, 600 mm in length
- \*3 Up to max. 18 cm in width, oak wood up to max. 20 cm in width
- \*4 Only on edge lamella from 22 mm in width

- \*5 Direct installation only with MS Parquet Adhesives
- \*6 On edge lamella parquet from 16 mm in width, max. 200 mm in length
- \*E All mentioned products are very low in emissions, except for \*E

Subfloor preparation of non suitable subfloors for direct bonding of parquet according to DIN 18356

Subfloors	Preparing	Prepare	Primer Dilution	Drying time	Bonding of reinforce- ment / decoupling	Reinforcement / decoupling	Primer Dilution	Drying time	Levelling
Cement screeds (CT), concrete with insufficient levelness		Grind and vacuum RS 5925, RS 5935 or RS 5945	D 3003 or D 3004 1:2 with water	when suitable for walking					A 830 Z 610 Z 615 Z 625 Z 630 Z 635 Z 715 Z 515
Calcium sulfate screeds (CA), with insufficient levelness		Grind and vacuum RS 5935 or RS 5945	D 3003 or D 3004 1:2 with water	approx. 1 hour when suitable for walking in combination with A 830					
Magnesite screeds (MA), with insufficient levelness		Grind and vacuum RS 5935 or RS 5945	PU 280 PU 235 MS 330	approx. 1 hour approx. 4-6 hours approx. 1 hour			D 3045	approx. 1 hour	
Mastic asphalt screeds (AS), with insufficient levelness		Vacuum RS 5925, RS 5935 or RS 5945	D 3004 1:1 with water or D 3045	approx. 30-60 minutes					
Terrazzo, tiles with insufficient levelness		Cleaning with R 4515, RS 5925, RS 5935 or RS 5945	D 3004 undiluted or D 3045	approx. 30-60 minutes					
Old adhesive remnants on standardised subfloors		Grind and vacuum RS 5925, RS 5935 or RS 5945	PU 280 PU 235 MS 330	approx. 1 hour approx. 4-6 hours approx. 1 hour			D 3045	approx. 1 hour	A 830 Z 610 Z 615 Z 625 Z 630 Z 635 Z 715 Z 515
Cement screeds (CT) with to high residual humidity up to 6 CM% / 98 % KRL without underfloor heating, up to 3 CM% / 85 % KRL with underfloor heating, concrete with to high residual humidity up to 7.5 % / 98 % KRL by weight		Grind and vacuum RS 5925, RS 5935 or RS 5945	PU 280 2-fold layer PU 235 2-fold layer	approx. 1 hour per layer approx. 4-6 hours per layer					
Cement screeds (CT) with to high residual humidity up to 5 CM% / 95 % KRL without underfloor heating, up to 3 CM% / 85 % KRL with underfloor heating, concrete with to high residual humidity up to 7 % / 95 % KRL by weight		Grind and vacuum RS 5925, RS 5935 or RS 5945	MS 330	approx. 1 hour					
Cement screeds (CT), concrete with insufficient surface stability		Grind and vacuum RS 5925, RS 5935 or RS 5945	PU 280 *1 PU 235 *1 MS 330 *1	approx. 1 hour approx. 4-6 hours per layer approx. 1 hour					
Cement screeds (CT) with to high residual humidity up to 5 CM% / 95 % KRL without underfloor heating, up to 3 CM% / 85 % KRL with underfloor heating		Grind and vacuum RS 5935 or RS 5945	D 3080 1:1 with water then D 3080 undiluted	at least 30 minutes  at least 120 minutes					A 830 Z 610 Z 615 Z 625 Z 630  Z 635 Z 715 Z 515
Cement screeds (CT), concrete, calcium sulfate screeds (CA), magnesite sceeds (MA) or mastic asphalt screeds (AS) sufficient load-bearing but with cracks or not homogeneous (different pavings)		Grind and vacuum	PU 280 PU 235 MS 330 *3	approx. 1 hour approx. 4-6 hours approx. 1 hour	MS 230 MS 232 MS 239 MS 258 MS 260 MS 261 MS 262 MS 265 MS 290 MS 292 MS 299 PU 210	PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	EM 140 *1 RP 104 *1 RP 107 *1 RP 109 *1 RP 115 *1 RP 704 *1 RP 707 *1 RP 709 *1 RP 715 *1 TS 102 *1 TS 103 *1 TS 112 *1		
Gypsum fibre boards, as far as parquet type is recommended for direct bonding by manufacturer		Vacuum			MS 228 MS 230 MS 232 MS 239 MS 258 MS 260 MS 261 MS 262 MS 265 MS 290 MS 292 MS 299 PU 210 PU 225 PU 385 PU 215 *E PU 216 *E PU 220 *E	EM 140 RP 104 RP 107 RP 109 RP 115 RP 704 RP 707 RP 709 RP 715 TS 102 TS 103 TS 112			
Permanent existinng tiles, wood planks, parquet		Cleaning of tiles with R 4515, sand entire surface			MS 228 MS 230 MS 232 MS 239 MS 258 MS 260 MS 261 MS 262 MS 265 MS 290 MS 292 MS 299 PU 210 PU 215 *E PU 216 *E PU 220 *E PU 385	EM 140 RP 104 RP 107 RP 109 RP 115 RP 704 RP 707 RP 709 RP 715 TS 102 TS 103 TS 112			
Permanent existinng tiles, wood planks, parquet		Cleaning of tiles with R 4515, sand entire surface							D 3060 *2 +  Z 645 *2 Z 610 *2 Z 615 *2 Z 625 *2 Z 630 *2 Z 640 *2
Installation lines to be levelled, levelling/filling of wooden floorboards and wooden beam compartments, levelling of areas with limited static load-bearing capacity (according to the planner's specifications)		Set up screed edge strips, lay out suitable foil for installation on separating layer, apply primer or bonding slurry to the subfloor, WAKOL Z 590 Light Screed		24 hours			AR 150 levelled with Z 640/Z645 mixed with D 3060		Z 515 Z 610 Z 615 Z 625 Z 630 A 830

The applicable standards and fact sheets must be heeded with all laying operations.

Please note:  
\*1 Depending on subfloor stability, in case of doubt please consult Wakol technical support  
\*2 If levelling is necessary

\*3 Direct installation only with MS Parquet Adhesives  
\*E All mentioned products are very low in emissions, except for \*E

Direct installation of cork flooring  
on standardised or renovated subfloors

Flooring	Subfloors	Cement screeds (CT) with sufficient smooth and level surface	Calcium sulfate screeds (CA) with sufficient smooth and level surface	Gypsum fibre boards	Wood based material boards Chipboards according to DIN EN 312 (P4 up to P7), OSB according to DIN EN 300 (OSB/2 up to OSB/4)	Newly levelled subfloors with Wakol cement based levelling compounds	WAKOL RP 104 Decoupling Sheet, 4 mm WAKOL RP 104 Decoupling Sheet, 7 mm WAKOL RP 109 Decoupling Sheet, 9 mm WAKOL RP 115 Decoupling Sheet, 15 mm WAKOL RP 704 Project Decoupling Sheet, 4 mm WAKOL RP 707 Project Decoupling Sheet, 7 mm WAKOL RP 709 Project Decoupling Sheet, 9 mm WAKOL RP 715 Project Decoupling Sheet, 15 mm
	Cork floorings with nature cork backing according to ISO 3813 respectively DIN EN 12104	MS 260 *1 MS 290 *1 MS 265 *1	MS 260 *1 MS 290 *1 MS 265 *1	MS 260 *1 MS 290 *1 MS 265 *1	D 3540 *2 MS 260 *1 MS 265 *1 MS 290 *1	D 3540 MS 260 *1 MS 265 *1 MS 290 *1	
	Cork floorings with HDF/MDF middle layer and cork stabilising layer	MS 258 MS 260 MS 261 MS 262 MS 265 MS 290 MS 292	MS 299 PU 385	MS 258 MS 260 MS 261 MS 262 MS 265 MS 290 MS 292	MS 299 PU 385	MS 258 MS 260 MS 261 MS 262 MS 265 MS 290 MS 292	MS 299 PU 385

The applicable standards and fact sheets must be heeded with all laying operations as well as manufacturer's instrutions.

Please note:  
\*1 Flat-lying cork floorings  
\*2 Not on OSB  
  
All mentioned products are very low in emissions



Subfloor preparation of non suitable subfloors for direct bonding of cork floorings according to DIN 18365























Subfloors	Preparing	Prepare	Primer Dilution	Drying time	Bonding of reinforce- ment / decoupling	Reinforcement / decoupling	Primer Dilution	Drying time	Levelling
Cement screeds (CT)		Grind and vacuum RS 5925, RS 5935 or RS 5945	D 3003 or D 3004 1:2 with water	when suitable for walking					Z 610 Z 615 Z 625 Z 630 Z 635 Z 675 Z 680 Z 715 Z 515
Calcium sulfate screeds (CA)		Grind and vacuum RS 5925, RS 5935 or RS 5945	D 3003 or D 3004 1:2 with water	approx. 1 hour					
Magnesite screeds (MA)		Grind and vacuum RS 5925, RS 5935 or RS 5945	PU 280 PU 235 MS 330	approx. 1 hour approx. 4-6 hours approx. 1 hour			D 3045	approx. 1 hour	
Mastic asphalt screeds (AS)		Vacuum RS 5925, RS 5935 or RS 5945	D 3004 1:1 with water or D 3045	approx. 30-60 minutes					
Terrazzo, tiles		Cleaning with R 4515, RS 5935 or RS 5945	D 3004 undiluted or D 3045	approx. 30-60 minutes					
Gypsum fibre boards		Vacuum RS 5925, RS 5935 or RS 5945	D 3003 or D 3004 1:2 with water	approx. 1 hour					Z 610 Z 615 Z 625 Z 630
Old adhesive remnants on standardised subfloors, waterproof and non-waterproof		Grind and vacuum RS 5935 or RS 5945	PU 280 PU 235 MS 330	approx. 1 hour approx. 4-6 hours approx. 1 hour			D 3045	approx. 1 hour	Z 610 Z 615 Z 625 Z 630 Z 635 Z 675 Z 680 Z 715 Z 515
Cement screeds (CT) with to high residual humidity up to 6 CM% / 98 % KRL without underfloor heating, up to 3 CM% / 85 % KRL with underfloor heating, concrete with to high residual humidity up to 7.5 % / 98 % KRL by weight		Grind and vacuum RS 5925, RS 5935 or RS 5945	PU 280 2-fold layer PU 235 2-fold layer	approx. 1 hour per layer approx. 4-6 hours per layer					
Cement screeds (CT) with to high residual humidity up to 5 CM% / 95 % KRL without underfloor heating, up to 3 CM% / 85 % KRL with underfloor heating, concrete with to high residual humidity up to 7 % / 95 % KRL by weight		Grind and vacuum RS 5925, RS 5935 or RS 5945	MS 330	approx. 1 hour					
Cement screeds (CT), concrete with insufficient surface stability		Grind and vacuum RS 5935 or RS 5945	PU 280 *1 PU 235 *1 MS 330 *1	approx. 1 hour approx. 4-6 hours approx. 1 hour					
Cement screeds (CT) with to high residual humidity up to 5 CM% / 95 % KRL without underfloor heating, up to 3 CM% / 85 % KRL with underfloor heating		Grind and vacuum RS 5925, RS 5935 or RS 5945	D 3080 1:1 with water then D 3080 undiluted	at least 30 minutes  at least 120 minutes					Z 610 Z 615 Z 625 Z 630 Z 635 Z 675 Z 680 Z 715 Z 515
Cement screeds (CT), concrete, calcium sulfate screeds (CA), magnesite sceeds (MA) or mastic asphalt screeds (AS) sufficient load-bearing but with cracks or not homogeneous (different pavings)		Grind and vacuum RS 5925, RS 5935 or RS 5945	PU 280 PU 235 MS 330 *2	approx. 1 hour approx. 4-6 hours approx. 1 hour	MS 290 MS 292 MS 299 PU 210 PU 225 PU 385	PU 215 *E PU 216 *E PU 220 *E	EM 140 *1 RP 104 *1 RP 107 *1 RP 109 *1 RP 115 *1 RP 704 *1 RP 709 *1 RP 715 *1		Z 610 Z 615 Z 625 Z 630 Z 515
Old, finished floors, permanent existing only tiles, wood planks, linoleum, parquet		Cleaning tiles with R 4515, sand entire surface RS 5925, RS 5935 or RS 5945			MS 290 MS 292 MS 299 PU 210 PU 225 PU 385	PU 215 *E PU 216 *E PU 220 *E	EM 140 RP 104 RP 107 RP 109 RP 115 RP 704 RP 709 RP 715		


















The applicable standards and fact sheets must be heeded with all laying operations.

Please note:  
\*1 For underfloor heating please consult Wakol technical support  
\*2 Direct installation only with MS Parquet Adhesives  
\*E All mentioned products are very low in emissions, except for \*E

Trowel Notch Sizes

A good adhesive adheres even better when used with the right applicator. Below is the selected series of notch sizes determined by the Technical Commission on Construction Adhesives (TKB). Notched trowels and strips according to the uniform TKB designation are supplied by all leading tool manufacturers.

		Notch depth mm		Notch width mm		Notch bridge width mm		Angle °
Group A								
A 1		1,1	1,5	0,5	55°			
A 2		1,4	1,7	1,3	55°			
Group B								
B 1		2,0	2,4	2,6	55°			
B 2		2,55	3,0	2,0	55°			
B 3		3,25	3,7	3,3	55°			
B 5		5,15	5,7	14,3	55°			
B 11		5,0	6,1	7,9	60°			
B 13		6,5	7,1	11,4	55°			
B 15		6,3	5,6	6,9	45°			
B 5 Specialty Trowel Blade		5,15	5,7	14,3	55°			

Group R								
R 2		5,0	4,0	2,0	R			
R 3		5,0	6,0	2,4	U			
R 4		6,0	6,0	2,4	U			
Group S								
S 2		3,35	4,2	0,1	60°			
Special notch sizes from Pajarito								
7		4,7	2,8	0,2				
25		3,8	5,7	0,3				

Symbols

The symbols describe the properties and applicability of the individual products:

			
Very low in emissions according to EMICODE EC1 PLUS	Very low in emissions according to EMICODE EC1	Emissions class i.a.w. Finnish law	Laying materials with low emissions according to DE-UZ 113
			
Emissions class i.a.w. French law	Classification systems in accordance with GISBAU	Solvent free according to TRGS 610	CE marking Council Directive 305/2011 EU
			
Emissions-tested building product in accordance with DIBt guidelines	Polish marking according to EN ISO 17178	Wheelmark Certification Council Directive 2014/90/EU	CONNECTED SYSTEMS Guarantee with Loba paints and/or oils
			
Suitable for underfloor heating	Suitable for wheelchairs	Conductive product	Suitable for installing sport flooring



EMICODE

EMICODE is a trademark-protected seal for product classification for modern, solvent-free and low-emission laying materials and construction products. These include, amongst others:

- Liquid products (coatings, primers, sealer- or barrier primers ready-to-use fluid fixations and adhesives, fluid sealings)
- Powdery products (cement and calcium-sulphate based levelling compounds, quick cement, screed, cement and calcium-sulphate based screed binders tile adhesive and joint mortar, mineral barrier coatings, cement and calcium-sulphate based screeds and screed binders)
- Pasty products and products with a high organic binder content (1-C or 2-C pasty flooring-, parquet and ready-to-use tile-adhesives, assembly adhesives, pasty fixations, dispersion- and reactive levelling compounds)
- Products which do not require a chemical reaction or physical drying (Underlay systems, e.g. insulating underlays, underlays with an adhesive coating, adhesive tapes, chipboards, decoupling-/insulating sheets)
- Sealing tapes and collars for small surfaces (e.g. for window, facade, in wet areas); Sealing membranes for large surfaces (e.g. for walls and floor in wet areas), vapour retarder under the roof

The inspection symbol for environmental and interior hygiene has been awarded since 1997 by the GEV (German Registered Association for the Control of Emissions in Products for Flooring Installation) to products of manufacturers who subject themselves to strict quality controls and regular inspections. With regard to consumer and processor protection, EMICODE provides an orientation aid for the assessment and selection of chemical construction products. The classification system is aimed at planners, consumers and tradesmen, is company-independent and competitively neutral.

The EMICODE breaks down into the following 3 emission classes, based on the strictly defined GEV test method (emissions test chamber) and the GEV classification criteria:

EMICODE EC1 PLUS	very low emission level PLUS
EMICODE EC1	very low emission level
EMICODE EC2	low emission level

Especially important is the best emission class, EMICODE EC1 PLUS. The TVOC thresholds for this class after 28 days are defined as follows:

EMICODE EC1 PLUS for primers, for levelling compounds and for adhesives as well as subfloors ≤ 60 µg/m³.

For details, see: [www.emicode.com](http://www.emicode.com)

Many Wakol line products correspond to the best emission class, EMICODE EC1. They are subjected to especially strict controls according to DIN EN ISO 9001:2015, from the raw material stage to manufacture, with respect to their emission characteristics as well as their superb, technical functionality.

Status 12/19

Blue Angel

The Blue Angel is awarded for different product categories in accordance with respectively adjusted inspection criteria. Laying materials are inspected in accordance with DE-UZ 113. After an external inspection of the emission characteristics and fulfilment of other conditions regarding content and container or datasheet information, the Blue Angel licence is awarded

by the German Institute for Quality Assurance and Marking (RAL). Marking with the Blue Angel is voluntary. For laying materials, in accordance with DE-UZ 113 there are Blue Angel criteria for products with low VOC emissions to interior air and thus with little effect on human health. For private end consumers, it is the most widely known eco-label. The requirements of the EMICODE EC1 and of the Blue Angel are comparable. EMICODE EC1 PLUS specifies the highest requirements with regard to low-emission laying materials, [www.blauer-engel.de/en/products/construction/bodenbelagsklebstoffe](http://www.blauer-engel.de/en/products/construction/bodenbelagsklebstoffe).

M1 Classification: Emission classification of building materials

M1 is a protected seal for product classification of low-emission building materials.

The voluntary Finnish test mark for environmental and indoor hygiene has been awarded since 1996 by the Building Information Foundation RTS to products of manufacturers who undergo strict quality controls as well as regular inspections. The aim of the classification is to promote the development and use of low-emission building materials.

The classification sets emission and odour requirements for building materials, furnishings and furniture in office and residential buildings with regard to indoor air quality. Emission and odour tests in a neutral third-party laboratory provide reliable information on the emissivity of building materials.

In the M1 classification, limit values are set for the emission and odour from the product into the indoor air. Levelling compounds must be casein-free.

Status 1/21

French VOC regulations

The French regulations on VOC emissions classes stipulate that from 1 January 2012 all construction products, flooring and wall surfaces, paints and lacquers used indoors must be marked with their emissions class. Categorisation of the emissions classes is to be on the basis of specified limit values and is the responsibility of the manufacturer. The marking on the product states the highest (worst) of the emissions classes determined for the VOCs and for the TVOC. Equivalent data on the emissions, for example from inspections for AgBB, EMICODE, Blue Angel etc. will be accepted. For details, see [www.wakol.com](http://www.wakol.com).

TRGS 610/Regulations on hazardous substances

The German regulations on hazardous substances (GefStoffV) comprehensively regulate the categorisation, marking and handling of all kinds of hazardous substances ([www.baua.de/de/Themen-von-A-Z/Gefahrstoffe/Rechtstexte/Gefahrstoffverordnung.html](http://www.baua.de/de/Themen-von-A-Z/Gefahrstoffe/Rechtstexte/Gefahrstoffverordnung.html)). The Technical Regulations on Hazardous Substances (TRGS) define the requirements of the regulations on hazardous substances for trades. Compliance with the TRGS means the requirements of the regulations on hazardous substances are fulfilled.

The TRGS 610 Alternative materials and alternative procedures for high solvent-based primers and adhesives for floorings have been updated. In accordance with the TRGS 610, solvent-free dispersion adhesives, SMP/MS adhesives and solvent-free PU adhesives are recommended as possible alternatives.

The full text of the TRGS 610 can be found at [wakol.com](http://wakol.com)

GISCODE

GISCODE is a classification system agreed on in 1993 by manufacturers and GermanBuilders'TradeAssociations(GISBAU)fordistinguishingproductgroups with certain common hazardous features. The system is exclusively geared to occupational safety and in large parts refers to the 4 product categories of the TRGS 610.

D1	solvent-free dispersion-based floor laying substances
GG60	basic cleaner, irritant (including eye damage), solvent-based with 2-butoxyethanol
RE30	Epoxide resin products, sensitizing, totally solid
RS10	Laying materials containing methoxysilane
RS20	Laying materials, primers / coatings containing mehtoxysilane
RS25	Laying materials, methoxysilane containing base / coating
RU1	solvent-free polyurethane floor laying substances
S1	high solvent level floor laying substances, non-aromatic and methanol-free
CP1	Calcium sulfate based levelling compounds
CP3	Calcium sulphate-based levelling compound, calcium oxide content bigger than 3 %
ZP1	Cement-based products, low in chromate

The classification according to GISCODE, e.g. on container labels, in product information and on safety data sheets, is carried out voluntarily in particular by member companies of the adhesive industrial association „Klebstoffe e.V.“ For all GISCODE product groups the corresponding product information and sample operational instructions are available from the construction professional associations. See [www.wingisonline.de](http://www.wingisonline.de)

Status 1/25

CE mark

The CE mark is a producer label, stating that the product complies with a harmonised European norm. For levelling compounds this is conformity with DIN EN 13813 „Screed material and floor screeds“. Using the CE mark a high level of transparency concerning important product properties. Each CE labelled product must meet all labelled criteria. The values therefore are always minimum values. According to the European Construction Products Regulation (EU 305/2011) a Declaration of performance has to be provided by the manufacturer for each CE labelled product. The declaration of performance can be found at [www.wakol.com](http://www.wakol.com).

Mark of conformity

The mark of conformity (Ü-Zeichen) designates laying materials that fulfil the relevant technical specifications of the building authorities. In Austria known as the „ÜA-Einbauzeichen“. General building authority approvals are granted for construction products and methods in the area of application as defined by the state building authorities. They are reliable proof of the usability of construction products. The German Institute for Building Technology (DIBt) is the German licensing authority for general building authority approvals for construction products.

For reasons of health protection, since 01.01.2011 adhesives for parquet and wooden flooring require general building authority approval for their use in habitable rooms (cf. Building Regulation List B Part 1, ser. no. 1.18.3 and Appendix 1/18.3). On 01.01.2012 approval for adhesives for floorings and underlays became a mandatory requirement.

Wheelmark

The Wheelmark is a mark of conformity valid throughout the EU, confirming suitability of the respective product for marine equipment in accordance with Council of the European Community Directive 2014/90/EU on marine equipment (EC Marine Equipment Directive – MED). To obtain this mark of conformity, a defined fire test must be passed. In addition to this EC type examination, monitoring measures carried out by an accredited body are required, e.g. a quality management system as per Module D. The support organisation for the Wheelmark is the IMO, International Maritime Organisation, an affiliate organisation of the UNO. The declaration of conformity for the corresponding products can be found at [www.wakol.com](http://www.wakol.com).

Environmental Product Declaration, EPD

An EPD is a data set which attempts to compile all environmentally relevant information/data like resource consumption and emissions to a product over the complete product life cycle. These are approx. 100 individual data. Starting point for making an EPD is the so called ecological balance sheet, thus a systematic analysis on the environmental impact of products during their complete life cycle. This is why it is also called life cycle analysis. The basic procedure for making such product declarations is partly regulated and expressed by standardized norms, e.g. EN 15804.

In order to compile these extensive data, assumptions, average values, estimations are made according to the product division.

The ISO-Type-III-Declaration according to DIN EN ISO 14025 has been created in cooperation with the Institute for Construction and Environment (Institut für Bauen und Umwelt e.V.). With these quantitative statements about the environmental performance of building products, EPDs are also used for certification of buildings, keyword “sustainable building“. In Germany, buildings are certified for example by the DGNB (Deutsche Gesellschaft für nachhaltiges Bauen = German sustainable building council). Depending on the fulfillment of the criteria, the DGNB awards certificates in gold, silver or bronze.

Quality Seal for Sustainable Buildings (QNG)

The German Quality Seal for Sustainable Buildings (QNG) is a state seal of quality for buildings, with the Federal Ministry of Housing, Urban Development and Building (BMWSB) as the seal issuer and accredited certification bodies as awarding bodies.

Wakol offers a comprehensive range of laying materials that fulfil the criteria for the requirements of the Quality Seal for Sustainable Buildings (QNG). The requirements are described in the QNG requirements catalogue Appendix document 313, version 1.3, Avoidance of harmful substances in building materials.

The product list and the declaration of conformity can be found at [wakol.com](http://wakol.com)



For more information:





# A STRONG CONNECTION FOR YOUR SUCCESS

Connected Systems  
Perfect results  
for your projects

- Your benefits with LOBA and Wakol Connected Systems**
- Outstanding compatible products
  - Maximum safety for your installation
  - Successful application guaranteed in a well proven system
  - No interactions
  - Long-term quality assurance through regular tests when adapting recipes
- We care about your success!

		WAKOL																		
		1K PARQUET ADHESIVE														2K PARQUET ADHESIVE				
		D 1640	D 1690	MS 228	MS 230	MS 232	MS 239	MS 260	MS 261	MS 262	MS 265	MS 290	MS 292	PU 299	PU 385	PU 210	PU 215	PU 216	PU 220	PU 225
LOBA   FINISHES	1K LACK	EasyFinish Neo	✓	✓				✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓
	EasyFinish	✓	✓					✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓
	Speed	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Viva	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	Life	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
LOBA   FINISHES	2K LACK	2K InvisibleProtect	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓
	2K Supra A.T.	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	2K Duo	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	2K Fusion	✓	✓					✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓
	2K Drive	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
LOBA   OILS	2K ImpactOil	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓
	2K ImpactOil Color	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓
	Akzent 100 Oil	✓	✓					✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓
	HardwaxOil EcoPlus	✓	✓					✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓	✓
	HardwaxOil	✓	✓							✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	HardwaxOil Nature	✓	✓								✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

		WAKOL		
		LEVELLING COMPOUND		
		Z 610	Z 615	Z 625
LOBA	FINISH SYSTEM	FactoryBase and 2K FactoryStyle	✓	✓



Status January 2025 | Subject to change without notice | Updates can be found at [www.loba.de/en](http://www.loba.de/en) and [www.wakol.com](http://www.wakol.com). Professional use of the listed Connected Systems products is a key factor for successful results. Please take note of the respective technical data sheets of the products used.





D 9905603 04/25 300133805 www.monoc-t.de

Wakol GmbH  
Bottenbacher Str. 30  
D-66954 Pirmasens  
Tel. +49 6331 8001 131  
Fax +49 6331 8001 890  
[www.wakol.com](http://www.wakol.com)



**wakol®**  
Anspruch verbindet