

Installation recommendation for laying floorings on VarioKomp - underfloor heating, 20 mm

new flooring	textile flooring	needle fleece flooring	linoleum	PVC-, CV-flooring LVT flooring	multilayer parquet
adhesive	WAKOL D 3304 WAKOL D 3308 WAKOL D 3310 WAKOL D 3311 WAKOL D 3312 WAKOL D 3360	WAKOL D 3304 WAKOL D 3308 WAKOL D 3310 WAKOL D 3311 WAKOL D 3312 WAKOL D 3360 WAKOL MS 552	WAKOL D 3304 WAKOL D 3311 WAKOL D 3318 WAKOL D 3360 WAKOL MS 552	WAKOL D 3307 WAKOL D 3316 WAKOL D 3317 WAKOL D 3318 WAKOL D 3319 WAKOL D 3320 WAKOL D 3360 WAKOL MS 550 WAKOL MS 552	WAKOL MS 228 WAKOL MS 230 WAKOL MS 232 WAKOL MS 239 WAKOL MS 260 WAKOL MS 262 WAKOL MS 290 WAKOL MS 292 WAKOL MS 299
levelling (if necessary)	WAKOL A 830 Levelling Compound in 3-5 mm layer thickness				
primer (when levelling)	WAKOL D 3004 Primer Concentrate, 1:2 diluted with water				
preparatory work	vacuum cleaning				
subfloor	Variotherm modular floor heating dryboard 20 mm, VarioKomp According on the manufacturer instructions installed, filled with compact filler				

The different, specific construction site conditions not known to us in advance exclude any claim from this information. We therefore recommend that you conduct your own tests.

The recognized rules of profession, the currently applicable standards, information sheets and the laying instructions of the flooring manufacturer must be observed.

Please note our technical information of the individual products. We are happy to answer any questions, likewise to advise construction details and recommendations.

With the publication of this recommendation, all previous versions become invalid.

Wakol GmbH, technical service, Bottenbacher Str. 30, 66954 Pirmasens. Phone.: +49 (0) 6331 8001-187. Fax: +49 (0) 6331 8001-852. www.wakol.com

30.04.2025