

Win with versatility!



WAKOL MS 290 Parquet Adhesive, shear-resistant

New – first shear-resistant MS-Parquet Adhesive

Universal – also for especially critical parquet

Safe – no interaction with paints

Practical – 18 months storage stability in new sealed packaging

Product:



WAKOL®
Anspruch verbindet



WAKOL MS 290 Parquet Adhesive, shear-resistant – for modern laying of parquet



Bonding all parquet and wood types with MS-Technology

WAKOL MS 290 Parquet Adhesive, shear-resistant is the first MS-Adhesive in the group of „hard parquet adhesives“ in accordance with DIN EN 17178. In addition, the requirements of the former DIN 281 for shear resistance are fully complied with.

WAKOL MS 290 Parquet Adhesive, shear-resistant is suitable for all parquet and wood types. This also includes such demanding installations as 10 mm solid-wood parquet, beech, or solid wood planks e.g. of 25 cm thickness.

On account of the high internal strength, the system ensures maximum protection against block tearing.

Interaction with paints ruled out

WAKOL MS 290 Parquet Adhesive, shear-resistant is free from plasticising substances, which means that the possibility of interaction with surface finish caused by the migration of adhesive components is eliminated. WAKOL MS 290 Parquet Adhesive, shear-resistant is of course thus included in the "Connected Systems" system guarantee in combination with Loba paints. Insurance protection exists across systems for the joint use of the systems.

Long durability thanks to sealed containers

WAKOL MS 290 Parquet Adhesive, shear-resistant is delivered in practical plastic buckets. A compound aluminium foil, firmly sealed with the edge of the container, ensures optimum protection against moisture and safeguards storage stability for at least 18 months.



Hardening in the unopened original container, resulting in material loss and additional work, is thus eliminated. Constant processing properties, in particular good coatability, are ensured throughout the entire storage period.

Benefits of WAKOL MS 290 Parquet Adhesive, shear-resistant

- For all parquet types
- Very good scoring stability
- Long open time
- Fast strength build-up – can be sanded after 24 hours
- Can be easily removed from painted parquet surfaces
- For flat-lying natural cork flooring and ready-to-lay cork parquet
- Especially long storage stability – 18 months
- Best emissions class – EMICODE EC1 PLUS

Please always observe the technical information before processing.