

WAKOL Z 645 Filling Compound, dust-reduced Sustainability datasheet

Emissions to ambient air

EC 1 LUS	Very low in emissions according to EMICODE EC1 PLUS
	EMICODE® is a trademark-protected seal for product classification for modern, solvent-free and low-emission laying materials, adhesives and construction products.
	It is based on the criteria of the GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.).
ÉMISSIONS DANS L'AIR INTÉRIEUR'	Emissions class i.a.w. French law
	According to the French VOC regulation, all construction products, floor and wall coverings, paints and varnishes used indoors are labelled based on their emissions class.
	Categorisation is to be on the basis of specified limit values and is the responsibility of the manufacturer.

Technical assessment

	GISCODE ZP1 – Cement-based products, low chromate
GISCODE ZP1	The GISCODE is a voluntary classification system, agreed between product manufacturers and construction trade associations.
	It distinguishes between product groups using certain common hazard characteristics.

	CE marking i.a.w. DIN EN 13813
CE	The CE marking is a marking by the manufacturer. For levelling compounds this is compliance with DIN EN 13813 "Screed material and floor screeds". Each product with a CE marking must comply with the stated requirements. According to the European Construction Products Regulation (EU 305/2011), a declaration of performance is required for every CE product.

Environment protection assessment

EPD i.a.w. ISO 14025 and EN 15804	Declaration number of Institute for Construction and Environment: EPD-DBC-20220217-IBF-EN
	The above-mentioned construction product complies with the general environmental product declaration (EPD) of the German Institute for Construction and Environment (IBU) with the declaration number
	EPD-DBC-20220217-IBF-EN This describes the environmental performance of the product for promoting sustainable construction.
Recycling capability	Recycling capability
	All Wakol packaging can be processed and recycled after complete emptying. Disposal of empty containers through Interseroh.

Sustainability datasheet 506700GB00 0823 WAKOL Z 645 Filling Compound, dust-reduced

Wakol GmbH Bottenbacher Straße 30 D-66954 Pirmasens Tel. +49 6331 8001 131 Fax +49 6331 8001 890 www.wakol.com



Wakol GmbH Industriestraße 5 A-6841 Mäder Tel. +43 5523 64 700 Fax +43 5523 64 700 64 www.wakol.at Wakol Adhesa AG/SA Bionstraße 5 CH-9015 St. Gallen Tel. +41 31 9210 755 Fax +41 31 9212 968 www.wakoladhesa.ch Wakol Foreco srl Via Kennedy 75 I-20010 Marcallo con Casone Tel. +39 02 9761 939 Fax +39 02 97 253 021 www.wakolforeco.it Loba-Wakol Polska Sp.z o.o. ul. Sławęcińska 16, Macierzysz PL-05-850 Ożarów Mazowiecki Tel. +48 22 436 24 20 Fax +48 22 436 24 21 www.loba-wakol.pl 2/5

Lecol Chemie B.V. Schutweg 6 NL-5145 NP Waalwijk Tel. +31 416 566 540 Fax +31 416 566 531 www.lecol.nl

Health protection

	MAL-Code: 00-4
MAL-Code Danish ranking system for occupational safety requirements regarding the inhalation of chemical products	The Danish system MAL CODE is used for paints, adhesives and other chemical products that are applied to surfaces. It is based on a code system with two digits. The first digit stands for the minimum safety requirements for the inhalation of the vapours of the product. The second digit describes the minimum safety requirements for skin or eye contact or swallowing.
	The calculation of the code number is based on the chemical composition of the product. The protection measures required for the respective numbers are described in the accompanying documents.

Building certification systems

Sustainable building is registering increasing market significance worldwide. Various building certification systems now exist, which pursue a common objective: Promote building with positive (or less harmful) effects on the environment, ideally in harmony with the environment.

Within the individual systems buildings are rated using a comprehensive list of criteria based on their possible environmental impacts. The rating generally includes requirements of construction products and materials which are used indoors.

System	Classification WAKOL Z 645 Filling Compound, dust- reduced
DGNB	Highest quality level acc. to criterion ENV 1.2
QNG	Satisfies the requirements of Annex Document Version 1.3, Pollutant Avoidance Building Material
LEED	Satisfies the requirements i.a.w. IEQ Credit 4.1 with regard to "low-emitting adhesives and sealants"
BREEAM	Satisfies the requirements i.a.w. "Hea 02 Indoor air quality"
Baubook	Declared in the product group "Filling compounds, levelling compounds for laying work", Product index: 1508 bb
BVB	Satisfies the requirements according to Category 6, "Emissions to indoor environment"
Nordic Ecolabel	Satiesfies the requiements of the Nordic Ecolabel "New buildings Generation 4"

Sustainability datasheet 506700GB00 0823 WAKOL Z 645 Filling Compound, dust-reduced

Wakol GmbH Bottenbacher Straße 30 D-66954 Pirmasens Tel. +49 6331 8001 131 Fax +49 6331 8001 890 www.wakol.com



Wakol GmbH Industriestraße 5 A-6841 Mäder Tel. +43 5523 64 700 Fax +43 5523 64 700 64 www.wakol.at Wakol Adhesa AG/SA Bionstraße 5 CH-9015 St. Gallen Tel. +41 31 9210 755 Fax +41 31 9212 968 www.wakoladhesa.ch Wakol Foreco srl Via Kennedy 75 I-20010 Marcallo con Casone Tel. +39 02 9761 939 Fax +39 02 97 253 021 www.wakolforeco.it Loba-Wakol Polska Sp.z o.o. ul. Slawęcińska 16, Macierzysz PL-05-850 Ożarów Mazowiecki Tel. +48 22 436 24 20 Fax +48 22 436 24 21 www.loba-wakol.pl Lecol Chemie B.V. Schutweg 6 NL-5145 NP Waalwijk Tel. +31 416 566 540 Fax +31 416 566 531 www.lecol.nl

3/5

DGNB

The certification system of the German Sustainable Building Council (DGNB) rates the sustainability of buildings across their entire life cycle.

Under criterion ENV 1.2 "Risks for the local environment", materials, (construction) products and preparations are classified with regard to their hazardous or harmful effect on people, flora and fauna.

Products marked with:

- GISCODE D 1, ZP1, RU 0,5, RU 1, RE 05, RE 10, RE 20, RE 30, or RS10 and
- EMICODE EC1 or EC1 PLUS

satisfy the requirements of the highest DGNB quality level.

QNG

The 'Quality Seal for Sustainable Buildings' (QNG) is a state seal of quality for buildings, with the Federal Ministry of Housing, Urban Development and Building (BMWSB) as the seal issuer and accredited certification bodies as awarding bodies.

The quality seal is applicable to products that fulfil the criteria in the QNG requirements catalogue, Annex Document 313, Version 1.3, Pollutant Avoidance in Building Materials.

LEED

The American LEED® model (Leadership in Energy and Environmental Design) is internationally acknowledged and demonstrates the building quality in terms of energy and ecological aspects. Adhesives and sealants, as well as sealing primers, are rated according to whether they comply with the defined VOC limit values for emissions to the ambient air when used on the construction site.

Products classified as EMICODE EC1 PLUS satisfy the requirements i.a.w. IEQ 4.1 (Indoor Environmental Quality) with regard to "low-emitting adhesives and sealants" in the territory outside of North America.

BREEAM

BREEAM (Building Research Establishment Environmental Assessment Method), developed in Great Britain, is an internationally used system for the sustainability rating of buildings. The effects of adhesives and sealants on the quality of the ambient air in buildings are examined under "Hea 02 Interior Air Quality".

Products classified as EMICODE EC1 PLUS meet the requirements for use indoors.

Wakol GmbH Bottenbacher Straße 30 D-66954 Pirmasens Tel. +49 6331 8001 131 Fax +49 6331 8001 890 www.wakol.com



Wakol GmbH Industriestraße 5 A-6841 Mäder Tel. +43 5523 64 700 Fax +43 5523 64 700 64 www.wakol.at

Sustainability datasheet 506700GB00 0823 WAKOL Z 645 Filling Compound, dust-reduced

Wakol Adhesa AG/SA Bionstraße 5 CH-9015 St. Gallen Tel. +41 31 9210 755 Fax +41 31 9212 968 www.wakoladhesa.ch Wakol Foreco srl Via Kennedy 75 I-20010 Marcallo con Casone Tel. +39 02 9761 939 Fax +39 02 97 253 021 www.wakolforeco.it Loba-Wakol Polska Sp.z o.o. ul. Slawęcińska 16, Macierzysz PL-05-850 Ożarów Mazowiecki Tel, +48 22 436 24 20 Fax +48 22 436 24 21 www.loba-wakol.pl 4/5

Schutweg 6

NI -5145 NP

www.lecol.nl

Lecol Chemie B.V.

Waalwijk Tel. +31 416 566 540

Fax +31 416 566 531

Baubook

Via the internet platform of the Austrian baubook GmbH, manufacturers can declare their building products online - with regard to ecological criteria, building physics and building ecology parameters as well as product group-dependent properties. The platform is operated by the Vorarlberg Energy Institute and IBO GmbH.

After successfully passing quality assurance, the products are listed at www.baubook.info.

BVB

The Swedish BVB system or "Swedish Building Materials Assessment (Byggvarubedömningen)" rates construction products in terms of their environmental impacts. Adhesives are viewed in Category 6 – Materials used on surfaces or applications where emissions to the ambient air may arise.

Products classified as EMICODE EC1 PLUS meet the requirements for use indoors.

Nordic Ecolabel

The Nordic Ecolabel is the national sustainability label of the Scandinavian countries. Products listed in the 'supply chain declaration portal' database fulfil the criteria of the Nordic Ecolabel 'New buildings Generation 4'.

Important information

All details are based on our findings and the stage of product development at the time of creation.

In addition, the notices in the technical information and safety datasheets must also be observed. They can be found together with the product datasheets in their latest version online at www.wakol.com.

All previous versions become invalid with the publication of this sustainability datasheet dated September 26th, 2024.

Sustainability datasheet 506700GB00 0823 WAKOL Z 645 Filling Compound, dust-reduced

Wakol GmbH Bottenbacher Straße 30 D-66954 Pirmasens Tel. +49 6331 8001 131 Fax +49 6331 8001 890 www.wakol.com



Wakol GmbH Industriestraße 5 A-6841 Mäder Tel. +43 5523 64 700 Fax +43 5523 64 700 64 www.wakol.at Wakol Adhesa AG/SA Bionstraße 5 CH-9015 St. Gallen Tel. +41 31 9210 755 Fax +41 31 9212 968 www.wakoladhesa.ch Wakol Foreco srl Via Kennedy 75 I-20010 Marcallo con Casone Tel. +39 02 9761 939 Fax +39 02 97 253 021 www.wakolforeco.it Loba-Wakol Polska Sp.z o.o. ul. Slawęcińska 16, Macierzysz PL-05-850 Ożarów Mazowiecki Tel. +48 22 436 24 20 Fax +48 22 436 24 21 www.loba-wakol.pl 5/5

Lecol Chemie B.V. Schutweg 6 NL-5145 NP Waalwijk Tel. +31 416 566 540 Fax +31 416 566 531 www.lecol.nl