

WAKOL MS 335 Repair Resin

Technical Information

Area of application

Fast-curing, silane-modified repair resin for

- Repairing hollow spots in parquet flooring

Irrespective of parquet adhesive used.

Special properties



- solvent-free as defined by TRGS 610
- odour-neutral

- 1) Based on the criteria of GEV (Association for Emission-controlled Laying Materials), classified as EMICODE EC1 PLUS: very low in emissions
- 2) Emissions class according to French law
- 3) Not applicable because emission characteristics substantially better than those of GISCODE S0,5
- 4) Suitable for underfloor heating
- 5) Suitable for exposure to castor wheels

Technical data

Raw material base:	Silane-modified polymer
Pot life:	approx. 15 - 20 minutes
Hardening time:	approx. 2 hours
Storage time:	12 months at room temperature
Storage temperature:	not sensitive to frost

Usage

Pinpoint hollow spots and generously mask around the drilling location in order to avoid contaminating the surface. Drill the hollow spot vertically, if necessary create additional bore holes, e.g. inspection hole.

Add 50 ml water with syringe provided to 600 ml WAKOL MS 335 Repair Resin and stir in homogeneously for at least one minute using a small paddle mixer.

Inject the mixture into the hollow spot within the pot time of 15 - 20 minutes until it is adequately filled.

Weigh down the surface areas for approx. 2 hours. After this time the bore hole can be properly sealed using normal methods.

Important

Processing not below floor temperature of +15 °C and room temperature of +18 °C, as well as room humidity preferably between 40 % and 65 %, maximum 75 %. All information is based on approx. 20 °C and 50 % relative air humidity. In cold weather, warm up all laying materials in a heated room before use.

The injection of hollow spots is a repair method requiring bore holes in parquet flooring. Depending on the type of wood and wood sorting, the sealed areas can be noticed by the user to a greater or lesser extent. Please clarify the restoration with your customer before commencing work.

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data.

We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the currently applicable codes must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at www.wakol.com.

This Technical Information of 29.08.2019 supersedes all previous versions.