

# WAKOL MS 245 Montinator

## Technical Information

### Area of application

Single-component, elastic assembly adhesive for bonding

- Wooden materials
- Metals
- Plastics
- Concrete
- Stone
- Decorative panels
- Wall covering
- Panelling
- wooden strips

### Special properties



1)



2)



3)

- can be painted over after curing
- fast-curing
- stable
- moisture-curing
- easy to work with

1) Emissions class according to French law

2) Laying materials containing methoxysilane

3) Solvent-free according to definition of the German Adhesives Association and TRGS 610

### Technical data

Raw material base:

MS Hybrid Polymer

Cleaning agent:

WAKOL RV 105 Neoprene Dilution, before adhesive sets

Open time:

5 - 10 minutes

Hardening time:	2.5 mm layer - 24 hours
Temperature resistance:	-40 °C up to +90 °C after curing
Application method:	with a suitable cartridge gun
Storage temperature:	between +5 °C and +25 °C, keep away from heat
Storage time:	12 months at room temperature
Marking according to Ordinance on Hazardous Substances:	see safety data sheet

## Subfloors

The subfloor as well as the room climate conditions must meet the requirements of the applicable standards and data sheets. The substrate to be bonded must be free of dust, grease and oil, and it must be stable and load-bearing. Sand in advance as needed.

## Usage

WAKOL MS 245 Montinator apply to the surface to be bonded in line form and join together within open time.

## Important

Particularly well suited to parquet, skirting boards, stair profiles, abutting edges, repair stages and closing connection joints.

WAKOL MS 245 Montinator cannot be processed at temperatures below +5 °C or above +40 °C.

We recommend testing in advance due to the large number of coating agents available on the market. The coating must be applied to the sealant within 4 hours.

We guarantee the uniform high quality of our products. All data is based on tests and many years of practical experience and refers to standardised conditions. The variety of materials used and the different construction site conditions, which lie beyond our control, preclude any claims based on this data. We therefore recommend making sufficient trials. Accompanying flooring manufacturer's instructions and the currently applicable codes must be observed. We gladly provide technical advice.

The product data sheets can be found in their latest version at [www.wakol.com](http://www.wakol.com).

This Technical Information of 06.04.2020 supersedes all previous versions.